

## GE Sensing COMMITMENT TO EXCELLENCE

GE Sensing, Crown Industrial Estate, Priorswood Road, Taunton, Somerset, TA2 8QY, UK Tel +44 (0) 1823 335200 Fax +44 (0) 1823 332637

TEST SPECIFICATION	PART	No. YQR Range	ISSUE: A
CUSTOMER: Various	DATI	E: 11 <sup>th</sup> March, 2010	QUANTITY:
Customer P/N:	ORIG	INATOR: M.J.Roberts	PAGE 1 OF 1

**DESCRIPTION:** PTC THERMISTOR INTENDED FOR USE AS AN OVER TEMPERATURE SENSOR.

А

## **MECHANICAL SPECIFICATION**

CONSTRUCTION: COATED CERAMIC DISC WITH THICK SILVER FILM ELECTRODES, BONDED TO OPEN ENDED TAG. UNINSULATED LEADWIRES.

DIMENSIONS in mm: SE

SEE DRAWING AND TABLE BELOW.



CHANGES SINCE LAST ISSUE: $\Delta$						
Issue :	Α					
Date :	11/03/10					

SERIAL No.YQR	ISSUE : A	CONTINUATION	PAGE NO. 2

## **ELECTRICAL SPECIFICATION**

Part No.	Reference	Maximum	Maximum	Minimum	
	Temperature T <sub>ref</sub>	Resistance @	Resistance @	<b>Resistance</b> @	
		25°C, Ω	T <sub>ref</sub> -15°C	T <sub>ref</sub>	
YQR100R060	60	100	330	470	
YQR100R070	70	100	330	470	
YQR100R080	80	100	330	470	
YQR100R090	90	100	330	470	
YQR100R100	100	100	330	470	
YQR100R110	110	100	330	470	
YQR100R120	120	100	330	470	
YQR100R130	130	100	330	470	
YQR330R060	60	330	1500	2200	
YQR330R070	70	330	1500	2200	
YQR330R080	80	330	1500	2200	
YQR330R090	90	330	1500	2200	
YQR330R100	100	330	1500	2200	
YQR330R110	110	330	1500	2200	
YQR330R120	120	330	1500	2200	
YQR330R130	130	330	1500	2200	

MAXIMUM APPLIED VOLTAGE Vmax: 25V

**NOTES:** Measuring current: 10mA max.