

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Assembly with base element for type 2 arresters of the VALVETRAB MS product range, with remote indication contact and field wire disconnect. Version for 3-mode protection of 2-wire signals.



#### **Product Features**

- Versions with and without floating remote indication contact
- 3-Mode equalizer protection
- Field wire disconnect



### Key Commercial Data

Packing unit	1 pc
Country of origin	Germany

#### **Technical data**

#### Note

Trade restriction	The products are offered exclusively for export outside the EU and the European Economic Area.
-------------------	--

### Classifications

#### eCl@ss

eCl@ss 5.1	27130801
eCl@ss 6.0	27130802
eCl@ss 8.0	27130802
eCl@ss 9.0	27130802
ETIM	

FUW

ETIM 4.0	EC002497
	05/23/2016 Page 1 / 4



## Classifications

ETIM ETIM 5.0 EC000381 Accessories Accessories Bridge Plug-in bridge - FBS 2-18 - 2801068 Plug-in bridge for cross-connections in the VAL-MS BE-AR terminal center, 2-pos., color: Red Wiring bridge - MPB 18/1-57 - 2809238 Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 57-pos. Wiring bridge - MPB 18/1- 2 - 2809209 Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 2-pos. Wiring bridge - MPB 18/1-12 - 2748593 Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 12-pos.

05/23/2016 Page 2 / 4



## Accessories

Plug-in bridge - FBS 2-18 - 2801068



Plug-in bridge for cross-connections in the VAL-MS BE-AR terminal center, 2-pos., color: Red

Insertion bridge

Insertion bridge - EB 56-18 - 3009299



Insertion bridge, Pitch: 18 mm, Number of positions: 56, Color: gray

Screwdriver tools

Screwdriver - SZS 0,8X4,0 VDE - 1212508



Screwdriver, slot-headed, VDE insulated, size: 0.8 x 4.0 x 100 mm, 2-component grip, with non-slip grip

Screwdriver - SZS 0,4X2,5 VDE - 1205037

Screwdriver, slot-headed, VDE insulated, size: 0.4 x 2.5 x 80 mm, 2-component grip, with non-slip grip

#### Spare parts



### Accessories

Type 2 surge protection plug - VAL-MS 75 VF ST - 2805318



Surge protection plug type 2 with series connection consisting of varistor and gas-filled spark gap for VAL-MS base element, thermal monitoring, visual fault warning.

#### Type 2 surge protection plug - VAL-MS 350 VF ST - 2856595



surge protection connector type 2 with series connection consisting of varistor and gas-filled spark gap for VAL-MS base element, thermal monitoring, visual fault warning. Design: 350 V AC

## Drawings



Circuit diagram



Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com