Product Data Sheet



ION-BLOCK-24V | Ion Generator

Part Number



Note: The 24V block can be utilized as a 12V block.

Product Dimensions (inches [cm])





Conforms to: UL STD 867 UL STD 2998

Certified to: CAN/CSA STD C22.2 NO. 187



Product Application

Hospitals | Nursing Homes | Schools | Animal Feeding and Processing Plants | Shopping Malls | Laboratories | Airports | Restaurants and Food Preparation Areas | Zoos | Casinos | Convention Centers and Arenas | Jails | Museums | Health Clubs | Churches and Synagogues

Airflow



* bi-directional airflow

Technical Data

Power Supply	See part number voltage
Power Consumption	10W @ 12V; 5W @ 24V
Output Voltage	+/- 3.5kV @ 12V; +/- 7.0kV @ 24V
Power Wiring Leads	35 inches in length
Mounting	Self tapping metal screws
Dimensions	3.16" x 1.16" x 2.27"
CFM	2,400 CFM
Ion Count	24.9 Million ions/cm3 @ 12V; 49.8 Million ions/cm ³ @ 24V/115V/230V
Weight	.5 lbs (.25 kg)



Jackson Control Serving the Midwest Market for Over 50 Years

Illinois I Indiana I Kentucky I Michigan I Ohio I Pennsylvania



BUILDING HEALTH SOLUTIONS

www.jacksoncontrol.com 1-800-772-9859