

Programmable DC Electronic Load

PEL-8000 Series



PEL series product is a new generation of DC electronic load, adopt new chip to achieve high speed and high precision design, provide 0.1 mV and 0.01 mA resolution (basic accuracy is 0.03%, the current rise of 2.5 A/us), with novel appearance, scientific and rigorous production technology, this one is more cost-effective compare to similar products. It can be widely used in the production line (phone charger, cell phone batteries, electric vehicle batteries, switch power supply, linear power supply), scientific research institutions, automotive electronics, aerospace, marine, solar batteries, fuel cells and other industries.

- CC , CV , CR , CP , short circuit, dynamic and other working modes
- Over voltage, overcurrent, overpower, overheating, polarity reverse protection
- High brightness vacuum VFD screen and display V,A,P simultaneously
- Accuracy of 0.1% Standard RS-232 SENSE
- Support external trigger input, output
- Automatic test function setting, more convenient operation
- RS - 232 interface. Optional special communication line connecting computer

Model		PEL-8150		PEL-8300					
Input Rating	Power	150W		300W					
	Current	0~30A		0~60A					
	Voltage	150V							
CC mode	Range	0-3A	0-30A	0-6A	0-60A				
	Resolution	0.1mA							
	Accuracy	0.03%+0.05%							
CV mode	Range	0.1-19.999V		0.1-150V					
	Resolution	1mV	10mV	1mV	10mV				
	Accuracy	0.03%+0.05%							
CR mode	Range	0.3Ω-10k	0.3Ω-5k	0.3Ω-10k	0.3Ω-5k				
	Resolution	16 bits							
	Accuracy	0.2%+0.2%		0.1%+0.1%					
CW mode	Range	0-150W	0-150W	0-300W	0-300W				
	Resolution	1mW	10mW	1mW	10mW				
	Accuracy	0.2%+0.2%							
V Measurement	Voltage	0-19.999V	0-150V	0-19.999V	0-150V				
	Resolution	0.1mV	1mV	0.1mV	1mV				
	Accuracy	0.015%0.05%FS	0.015%0.05%FS	0.015%0.03%FS	0.015%0.02%FS				
C Measurement	Current	0-3A	0-30A	0-6A	0-60A				
	Resolution	0.1mA	1mA	0.1mA	1mA				
	Accuracy	0.03%+0.05%FS	0.03%+0.08%FS	0.03%+0.05%FS	0.03%+0.08%FS				
W Measurement	Watt	100W	150W	100W	300W				
	Resolution	1mW	10mW	1mW	10mW				
	Accuracy	0.2%+0.2%		0.1%+0.1%					
Battery Measurement Battery Input : 0.5-150V Max.Measurement:capacity=999/H;Resolution=0.1mA;Time=Range=1S-16HS									
Dynamic Measurement TransitionList: 0-25Khz;2.5A/us ; T1&T2: 60Us-999S;Accuracy: ±15%offset+10%FS									
1mS;2mS;5mS;10mS;20mS;50mS;100mS;200mS;Accuracy:±15%offset+10%FS									
Short circuit	Current(CC)	3A	30A	6A	60A				
	Voltage(CV)	0V							
	Resistance(CR)	55mΩ	25mΩ	300mΩ					
Temperature	Operating	0-40°C							
	Environment	-10°C~70°C							
Net weight	kg	4.1		4.9					
Gross weight	kg	5		5.8					
Instrument size (W*H*D)	mm	215*100*355							
Packing size (W*H*D)	mm	310*200*480							