



SBM3060UCT

EXTREME LOW VF SCHOTTKY RECTIFIER


VOLTAGE **60 Volt** **CURRENT** **30 Ampere**

FEATURES

- Extreme low forward voltage drop, low power loss
 - High efficiency operation
 - Lead free in compliance with EU RoHS 2011/65/EU directive
 - Green molding compound as per IEC61249 Std. . (Halogen Free)

MECHANICAL DATA

- Case : TO-220AB, Plastic
 - Terminals : Solderable per MIL-STD-750, Method 2026
 - Weight: 0.067 ounces, 1.89 grams.



MAXIMUM RATINGS($T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	VALUE	UNIT
Maximum repetitive peak reverse voltage	V _{RRM}	60	V
Maximum average forward rectified current	per diode per device	I _{F(AV)} 15 30	A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load	per diode	I _{FSM}	250
Typical thermal resistance per diode	(Note 1)	R _{θJC}	2
Operating junction temperature range	T _J	-55 to + 150	°C
Storage temperature range	T _{STG}	-55 to + 150	°C

Note : 1. Mounted on infinite heatsink.

ELECTRICAL CHARACTERISTICS($T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNIT
Breakdown voltage per diode	V _{BR}	I _R =1mA	60	-	-	V
Instantaneous forward voltage per diode	V _F	I _F =3A	-	0.33	-	
		I _F =7.5A	25°C	0.41	-	V
		I _F =15A	-	0.51	0.56	
	I _R	I _F =3A	-	0.25	-	
		I _F =7.5A	125°C	0.37	-	V
		I _F =15A	-	0.51	-	
Reverse current per diode	I _R	V _R =48V	-	100	-	µA
		V _R =60V	25°C	0.15	0.5	mA
			125°C	26	-	mA



SBM3060UCT




Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics




Fig.4 Typical Forward Characteristics




Fig.5 Operating Temperature Derating Curve




SBM3060UCT

Part No_packing code_Version

SBM3060UCT_T0_00001

For example :

RB500V-40_R2_00001

- Part No. 
- Serial number
- Version code means HF
- Packing size code means 13"
- Packing type means T/R

Packing Code XX				Version Code XXXXX		
Packing type	1 st Code	Packing size code	2 nd Code	HF or RoHS	1 st Code	2 nd ~5 th Code
Tape and Ammunition Box (T/B)	A	N/A	0	HF	0	serial number
Tape and Reel (T/R)	R	7"	1	RoHS	1	serial number
Bulk Packing (B/P)	B	13"	2			
Tube Packing (T/P)	T	26mm	X			
Tape and Reel (Right Oriented) (TRR)	S	52mm	Y			
Tape and Reel (Left Oriented) (TRL)	L	PANASERT T/B CATHODE UP (PBCU)	U			
FORMING	F	PANASERT T/B CATHODE DOWN (PBKD)	D			



SBM3060UCT

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.