SIEMENS

Data sheet

6GK5812-1BA00-2AA2

product type designation



M812-1 ADSL2+ (Annex B)

SCALANCE M812-1 ADSL router; for wire-bound IP communication from Ethernet- based automation devices via Internet service provider; VPN, Firewall, NAT; 1x Ethernet RJ45 port, 1x digital input, 1x digital output; ADSL2+, Annex B.

transfer rate		
transfer rate	10 Mbit/s, 100 Mbit/s	
transfer rate		
 for ADSL2+ transmission / with downlink / maximum 	25 Mbit/s	
 for ADSL2+ transmission / with uplink / maximum 	1.4 Mbit/s	
interfaces		
number of electrical connections		
 for internal network 	1	
 for external network 	1	
number of electrical connections		
for power supply	2	
type of electrical connection		
 for internal network 	RJ45 port (10/100 Mbit/s, TP, autocrossover)	
 for external network 	RJ45 DSL Port	
 for power supply 	Terminal strip	
WAN connection		
type of WAN connection / is supported	ADSL, ADSL2, ADSL2+	
operating mode for ADSL2/ADSL2+ / is supported	Annex B, Annex J	
supply voltage, current consumption, power loss		
supply voltage / rated value	24 V	
supply voltage / rated value	10.8 28.8	
type of voltage / of the supply voltage	DC	
consumed current		
 at rated supply voltage / maximum 	320 mA	
power loss [W]		
• maximum	8 W	
ambient conditions		
ambient temperature		
 during operation 	0 60 °C	
during storage	-40 +70 °C	
relative humidity / at 25 °C / during operation / maximum	95 %	
protection class IP	IP20	
design, dimensions and weights		
design	compact	
depth	127 mm	
height	147 mm	
width	35 mm	
net weight	400 g	

fastening method	
-	Yes
 35 mm top hat DIN rail mounting S7-300 rail mounting 	Yes
S7-1500 rail mounting	Yes
wall mounting	Yes
product features, product functions, product components	
product function	
DynDNS client	Yes
no-ip.com client	Yes
product functions / management, configuration, engineeri	ing
product function	
• CLI	Yes
 web-based management 	Yes
MIB support	Yes
TRAPs via email	Yes
protocol / is supported	
Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
type of configuration	Web-based management
product functions / diagnostics	
protocol / is supported	
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v2c	Yes
• SNMP v3	Yes
product function	
 statistics Packet Size 	No
 statistics packet type 	No
 error statistics 	No
• SysLog	Yes
packet filter log	Yes
product functions / DHCP	
product function	
DHCP client	Yes
DHCP server - internal network	Yes
product functions / routing	
router function	
 NAT (IP masquerading) 	Yes
 port forwarding 	Yes
NAT traversal	Yes
• 1:1 NAT	Yes
DNS cache	Yes
product functions / security	
suitability for operation / Virtual Private Network	Yes
firewall version	Statefull Inspection
product function	
password protection	Yes
• packet filter	Yes
broadcast/multicast/unicast limiter	No
product function	Ne
broadcast blocking	No
with VPN connection	IPsec, OpenVPN (as Client)
number of possible connections / with VPN connection	20
type of authentication / with Virtual Private Network / PSK	Yes
protocol / is supported	Voc
IPsec tunnel and transport mode	Yes
key length	
 1 / with IPsec AES / with Virtual Private Network 	128 bit

	400.1.1
• 2 / with IPsec AES / with Virtual Private Network	192 bit
• 3 / with IPsec AES / with Virtual Private Network	256 bit
with IPsec 3DES / with Virtual Private Network	168 bit
type of Internet key exchange / with Virtual Private Network	
main mode	Yes
quick mode	Yes
type of packet authentication / with Virtual Private Network	MD5, SHA-1, SHA-256, SHA-384, SHA-512
IETF profile / with Virtual Private Network / X.509v3 certificate	Yes
product functions / time	
protocol / is supported	
• NTP	Yes
• SNTP	Yes
standards, specifications, approvals	
standard	
• for EMC	EN 55022, EN 55024
• for FM	FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4
 for hazardous zone 	EN 60079-15, EN 60079-0, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X
 for safety / from CSA and UL 	UL E115352 Vol. X2
• for hazardous zone / from CSA and UL	ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, CL. 1, Div. 2, GP. A,B,C,D, T4 / CL. 1, Zone 2, GP IIC
 for emitted interference 	EN 55022 Class A
 for interference immunity 	EN 55024
certificate of suitability	
CE marking	Yes
CCC approval	Yes
further information / internet-Links	
Internet-Link	
 to website: Industrial communication 	http://www.siemens.com/simatic-net
 to website: Industry Mall 	https://mall.industry.siemens.com
 to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
 to website: Selection guide for cables and connectors 	http://www.siemens.com/snst
 to website: Image database 	http://automation.siemens.com/bilddb
 to website: CAx-Download-Manager 	http://www.siemens.com/cax
 to website: Industry Online Support 	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
last modified:	4/29/2021 🖸