



#### FEATURES:

- High Voltage (70V)
- · Low Forward Voltage
- · Various Dual Pair Configurations

MAXIMUM RATINGS: (T <sub>A</sub> =25°C)	SYMBOL		UNITS
Peak Repetitive Reverse Voltage	V <sub>RRM</sub>	70	V
Continuous Forward Current	١ <sub>F</sub>	15	mA
Peak Forward Surge Current, tp=1.0s	IFSM	50	mA
Power Dissipation	PD	250	mW
Operating and Storage Junction Temperature	TJ, Tstg	-65 to +150	°C
Thermal Resistance	$\Theta_{JA}$	500	°C/W

## ELECTRICAL CHARACTERISTICS PER DIODE: (TA=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
I <sub>R</sub>	V <sub>R</sub> =50V		10	200	nA
BVR	Ι <sub>R</sub> =10μΑ	70			V
V <sub>F</sub>	I <sub>F</sub> =1.0mA		395	410	mV
CJ	V <sub>R</sub> =0, f=1.0MHz			2.0	pF
t <sub>rr</sub>	I <sub>R</sub> =I <sub>F</sub> =10mA, I <sub>rr</sub> =1.0mA, R <sub>L</sub> =100Ω			5.0	ns

Central Semiconductor Corp.

www.centralsemi.com

## DESCRIPTION:

The CENTRAL SEMICONDUCTOR CMLD6263A series incorporates two pair, high voltage, low V<sub>F</sub> silicon diodes in a space saving SOT-563 surface mount package. These diodes are designed for fast switching applications requiring a low forward voltage drop.

MARKING CODES: CMLD6263A: 63A or 3A CMLD6263C: 63C CMLD6263S: 63S or 3S

R6 (11-December 2015)





## SOT-563 CASE - MECHANICAL OUTLINE



DIMENSIONS				
	INCHES		MILLIM	ETERS
SYMBOL	MIN	MAX	MIN	MAX
А	0.0027	0.007	0.07	0.18
В	0.0	800	0.	20
С	0.017	0.024	0.45	0.60
D	0.059	0.067	1.50	1.70
E	0.0		0.	50
F	0.059	0.067	1.50	1.70
G	0.043	0.051	1.10	1.30
Н	0.006	0.012	0.15	0.30
		SC	DT-563 (F	REV: R2)



3

2

COMMON ANODE

CMLD6263A

LEAD CODE:

1) Cathode D2

3) Cathode D44) Cathode D3

2) Anode D2, D4

5) Anode D1, D3

MARKING CODE: 63A or 3A

6) Cathode D1

PIN CONFIGURATIONS



#### CMLD6263C COMMON CATHODE

## LEAD CODE:

1) Anode D1 2) Anode D2 3) Cathode D3, D4 4) Anode D4 5) Anode D3 6) Cathode D1, D2

#### MARKING CODE: 63C



CMLD6263S IN SERIES

## LEAD CODE:

- 1) Cathode D2
- 2) Anode D3
- 3) Cathode D4
- 4) Cathode D3, Anode D4
- 5) Anode D1
- 6) Cathode D1, Anode D2

## MARKING CODE: 63S or 3S

R6 (11-December 2015)

www.centralsemi.com

Ο

1







## TYPICAL ELECTRICAL CHARACTERISTICS

www.centralsemi.com

R6 (11-December 2015)







## TYPICAL ELECTRICAL CHARACTERISTICS

www.centralsemi.com

R6 (11-December 2015)

## **OUTSTANDING SUPPORT AND SUPERIOR SERVICES**



## **PRODUCT SUPPORT**

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options

- Custom bar coding for shipments
- Custom product packing

## DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities

- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

## CONTACT US

## **Corporate Headquarters & Customer Support Team**

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA Main Tel: (631) 435-1110 Main Fax: (631) 435-1824 Support Team Fax: (631) 435-3388 www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors: www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: <u>www.centralsemi.com/terms</u>

www.centralsemi.com





http://www.centralsemi.com

# Product End of Life Notification

PDN ID:	PDN01063
Notification Date:	2/06/17
Last Buy Date:	N/A
Last Shipment Date	N/A

# Please be advised that Central Semiconductor must immediately discontinue the product(s) listed in the attached PDN notice. We are unable to accept any further orders for these products **unless** we have available inventory on hand.

You may have purchased one or more of the products listed. Please do not hesitate to contact your local Central Semiconductor sales representative with any questions or needs you may have. Central regrets any inconvenience this may cause.

Sincerely,

Central Semiconductor Corp.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.



http://www.centralsemi.com

## Product End of Life Notification

PDN ID:	PDN01063
Notification Date:	2/06/17
Last Buy Date:	N/A
Last Shipment Date	N/A

Summary:All devices manufactured in the SOT-563 package, using the Option 2 Lead Frame, are discontinued and now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by various manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's Product Management Process. Any replacement product will be noted below. The effective date for placing the last purchase order will be six(6) months from the date of this notice and twelve(12) months from the notice date for final shipments; this may be extended if inventory is available.

Central Part Number	Replacement
CMLD2004G TR	N/A
CMLD4448 TR	N/A
CMLD6001 TR	N/A
CMLD6263 TR	N/A
CMLD6263S TR	N/A
CMLSH-4 TR	N/A
CMLZDA3V3 TR	N/A
CMLZDA6V2 TR	N/A

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to engineering@centralsemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.