
Data sheet | Item number: 706-3033/102-300

System cable; for Schneider Modicon TM3; 8 digital inputs for higher

voltages; Length: 3 m; Conductor cross-section: 0.34 mm²

www.wago.com/706-3033/102-300





Color coding acc. to DIN VDE 47100		WAGO 231 series		PLC connector	
		Pin number	Wiring	Pin number	Signal
White		1	0.0	1	IN0
Brown		2	0.1	2	IN1
Green		3	0.2	3	IN2
Yellow		4	0.3	4	IN3
Grey		5	0.4	7	IN4
Pink		6	0.5	8	IN5
Blue		7	0.6	9	IN6
Red		8	0.7	10	IN7
Black		9	L	nc	nc
Violet		10	N	5-11	com0
Grey-Pink		11	nc	nc	nc
Red-Blue		12	nc	nc	nc

Data Notes

Note

If less than 3 channels are used simultaneously, the maximum current per conductor is 2 A and up to 5 A (30°C ambient temperature) or 3.5 A (50°C ambient temperature) at pins N/L. If more than 3 channels are used simultaneously, the maximum current per conductor is 0.75 A and up to 5 A (30°C ambient temperature) or 3.5 A (50°C ambient temperature) at pins N/L.

Electrical data

Inputs/outputs	8 digital inputs; for higher voltages	
Operating voltage	≤ AC/DC 250 V	
Current per wire (max.)	0.75 A	

Compatibility

 $\label{thm:continuity} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

Data sheet | Item number: 706-3033/102-300

www.wago.com/706-3033/102-300



Schneider

Schneider Modicon TM3	TM3 DI8A		
Connection data			
Connection data			
Cable type	LiYY		
Color code	per DIN VDE 47100		
Connection 1			
Connector	WAGO 231 Series		
Pole number 1	12		
Connection type 1	System		
Wire cross-section	0.34 mm²		
Connection 2			
Connector 2	TM3 DI8A		
Pole number 2	11		
Connection type 2	System		
Physical data			
Cable length	3 m		
Material Data			
Weight	429 g		
Environmental requirements			
Ambient temperature (operation)	-20 +50 °C		
Commercial data			
ETIM 8.0	EC000237		
ETIM 7.0	EC000237		
PU (SPU)	1 pcs		
Packaging type	bag		
Country of origin	FR		
OTINI			

 $\label{thm:continuity} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG

Hansastr. 27 32423 Minden

GTIN

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products?

4055143979931

We are always happy to take your call at +49 (571) 887-44222.

Data sheet | Item number: 706-3033/102-300

www.wago.com/706-3033/102-300



Customs tariff number 85444290900

Environmental Product Compliance

RoHS Compliance Status Compliant, No Exemption

Downloads

Documentation

System Description

WAGO System Wiring, Selection Guide

This guide will help you select the appropriate interface modules and system cables

for the controller you are usng.

pdf

545.9 kB

Download

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 706-3033/102-300

System cable; for Schneider Modicon TM3; 8 digital inputs for higher voltages;

Length: 3 m; Conductor cross-section: 0.34 mm²

URL

Download

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.