NSYTBS885

ABS box IP66 IK07 RAL7035 Int.H80W80D65 Ext.H89W89D51 Opaque cover H10





Main

Range	Thalassa
Product name	Thalassa TBS
Device Application	Multi-purpose
Category	Industrial box
Height	3.50 in (89 mm)
Width	3.50 in (89 mm)
Depth	2.13 in (54 mm)
Internal height	3.15 in (80 mm)
Internal width	3.15 in (80 mm)
Internal depth	1.85 in (47 mm)
Enclosure mounting	Wall mounted
Device composition	1 body
	1 cover 4 cover screw
Quantity per Set	Set of 5
Body type	One piece moulded
Type of front cover	Low plain cover
Cover fixing	Metal screws
Lock type	Captive screw flat outside sealed area
Removable parts	Cover by captive screws

Complementary

Material	ABS (acrylonitrile butadiene-styrene)	
Color	Gray RAL 7035)	
Standards	IEC 62208	
Product Certifications	TÜV	
Electrical Insulation Class	Class II	
IP degree of protection	IP66 conforming to NEMA 4.4X	
IK degree of protection	IK07 IEC 62262	
Glow wire resistance	1202 °F (650 °C) IEC 60695-2-11	
Ambient Air Temperature for Storage	5104 °F (-1540 °C)	
Operating temperature	-13140 °F (-2560 °C)	
Net Weight	0.21 lb(US) (0.096 kg)	

Ordering and shipping details

Category	80033-ENCLOSURE SYSTEMS POLYESTER
Discount Schedule	ES1
GTIN	3606480165214
Nbr. of units in pkg.	1
Package weight(Lbs)	2.84 oz (80.41 g)
Returnability	No
Country of origin	HU

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.17 in (5.5 cm)
Package 1 width	3.54 in (9.0 cm)
Package 1 Length	3.54 in (9.0 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	160
Package 2 Weight	34.35 lb(US) (15.58 kg)
Package 2 Height	15.75 in (40.0 cm)
Package 2 width	15.35 in (39.0 cm)
Package 2 Length	23.62 in (60.0 cm)
Unit Type of Package 3	BB1
Number of Units in Package 3	5
Package 3 Weight	16.19 oz (459.0 g)
Package 3 Height	3.74 in (9.5 cm)
Package 3 width	3.74 in (9.5 cm)
Package 3 Length	11.42 in (29.0 cm)

Offer Sustainability

Green Premium product
☐ REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
Yes
₫Yes
China RoHS Declaration
Product Environmental Profile

Contractual warranty

	· · ·	
Warrantv	18 months	
vvarranty	10 Horitis	
•		