





TH 310 Specifications
73310
deflector
1400°F (750°C)
38 ml
standard butane fuel triple filtered
up to 100 min continuous use (on mid setting)
piezo electronic system with 15 sec. heat-up
0.8" (19.9 mm)
0.2 lb (3.7 oz)
5.3" x 4.0" x 1.5" (l x w x d)
dimensions: 12.0" x 4.0" x 1.5" weight: 0.3 lbs (4.8 oz)
one year limited
CE, RoHs Compliant

ThermaHeat[™] 310

The ThermaHeatTM 310 is a high output flameless heat tool that offers rapid heat-up for immediate use. The tool is completely cordless and features adjustable heat output up to 1400°F (750°C) and a removable deflector for shrink tube installation.

Applications

General heating & drying, pvc bending, carmalizing creme brulee, plumbing, brazing, prosthetics, installing thin walls, adhesive line heat shrink tubing, soldering and desoldering

Key Features:

- High-grade quality materials
- Professional tools at an attractive price point
- Completely portable



Triple Filtered Butane BT 01 - 1 oz (28.4gm) No. 70001 BT 05 - 5 oz (142gm) No. 70005













www.steinel.net

(800) 852-4343 9051 Lyndale Avenue South, Bloomington, MN 55420

Automotive Repair

ino-nopali

L-80310