


THE REVISION STATUS OF ALL SHEETS OF THIS DRAWING IS THE SAME AS SHEET 1

LTR	DESCRIPTION	DATE	BY
-	Released	9/1/94	JP
B	Updated	8/22/07	JCL



**I. MATERIALS & FINISHES**

center contact: Gold Plated Beryllium Copper  
 outer contact: Alballoy Plated Brass  
 body: Alballoy Plated Brass  
 dielectric: Teflon® PTFE  
 gasket: Silicone Rubber  
 shrink sleeve: Adhesive Lined Polyolefin  
 attachment: braid clamp

**II. ELECTRICAL PROPERTIES**

impedance: 50 ohms  
 working voltage: 1000 vrms (max)  
 vswr: 1.25:1 (max) up to 2.5 GHz  
 insertion loss: 0.10 x √Fghz

Unless otherwise specified, dimensions are in inches. Tolerances are applicable when specified.

These drawings and specifications contain proprietary information which is the property of Times Microwave Systems.

Approvals		
Drawn	JP	9/1/94

**TIMES MICROWAVE SYSTEMS**  
 Wallingford, CT 06492  
 (203) 949-8400; (203) 949-8423.Fax  
 www.timesmicrowave.com

**TC-500-NFC**  
 Type-N female (jack)  
 for 500 Series Cables

Size A	CAGE CODE <b>68999</b>	Drawing No.: <b>3190-215</b>
Scale: NA		Rev. (B)
Sheet: 1 of 1		