

JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE 5600°K (RGB)	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF4142-20B	$x = 0.337 \pm .03$ $y = 0.368 \pm .03$	800	260	5	9,500 ± 10%	20,000

^{*} RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS		COMPONENTS CORPORATION						ION
			THIRD ANGLE PROJECTION	OTHERWISE: 1 PL +/- 2 PL +/- ANGLE +/-	0 0	TITLE	FLU	GLE LEAD T ORESCENT		MINIAT	URE	
Α	ADD x & y COORDINATED	7/5/06	DRAWN BY L. WENGSTROM	APPV'D BY L. R.	DATE 7/5/06	SIZE A	55335	DRAWING NO.	8F4142	-20B		
REV. NO.	RELEASED TO CAD DESCRIPTION/ECO NUMBER	9/17/02 APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE	NONE	RELEASED DATE 9/17/02	REVISION DATE	7/5/06	NO. A	SHEET 1 OF 1	