HellermannTyton

Specification Sheet

Part Number: 132-00009



Unique two piece tie allows parallel entry and exit through the head for easy assembly.

High impact, heat stabilized material gives strength needed for trucking and heavy equipment applications.

Button Head Cable Tie with Retainers and Pilot Bushings, 15.0" Long, PA66HIRHSUV, Black, 50/pkg

Article Number 132-00009

Type BT130LDP

Color Black (BK)

Quantity Per bag

Product DescriptionThe button head tie is a two piece tie providing for parallel entry and

exit through the head. The strap contains serrations on both sides, and has two opposed pawls recessed within a domed head. This design allows the strap to be directed clockwise or counter-clockwise

prior to insertion into the head, enabling bi-directional looping.

Short DescriptionButton Head Cable Tie with Retainers and Pilot Bushings, 15.0"

Long, PA66HIRHSUV, Black, 50/pkg

Minimum Tensile Strength (Imperial)	130.0
Minimum Tensile Strength (Metric)	578.0
Length L (Imperial)	15.0
Length L (Metric)	381.5
Fixation Method	Connector Clip
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Tie Closure Variant	plastic pawl Outside Serrated
Variant	Outside Serrated
Variant Width W (Imperial)	Outside Serrated 0.3
Variant Width W (Imperial) Width W (Metric)	Outside Serrated 0.3 7.6

110.0

Bundle Diameter Max (Metric)

Mounting Hole Diameter D (Metric) 25.4 mm

Material Polyamide 6.6 high impact modified, heat and UV stabilized

(PA66HIRHSUV)

PA66HIRHSUV **Material Shortcut**

Material Head Polyamide 6.6 heat stabilized (PA66HS)

Flammability UL 94 HB

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 50

Package Quantity (Metric) 50

Customs Number 3926909988