т	۵	п	m	0







LAYOUT SHOWN AS

Keying Shown as example

L

С

CHARACTERISTICS

ယ

 \sim

-Mass

BASIC SERIES:

SHELL SIZE : 11

Н

SHELL TYPE : Square Flange Receptacle

CONTACT TYPE : Standard Crimp Contact

PLATING : J = Olive drab Cadmium

-Standard : Based on MIL-DTL-38999 Series III

-Shell Material	: Composite	
-Shell Plating	: Olive drab Cadmium	
-Insulator	: Thermoplastic	
-Contacts	: Copper Alloy	
-Seals & Grommet	: Silicon Elastomer	
-Contact Plating	: Gold over copper Alloy 0.8µm minimum	
-Durability	: 500 Mating cycles	
-Delivered without Souriau contacts		
-Temperature Range	-65℃ to +175℃	
-Salt Spray	: 2000 hours	

: 10.6 g ± 10%

8D 0

G

11

J

22

S

F

Connector dimension			
Dim	Nominal		
Р	3.25±0.2		
PP	4.93±0.2		
R1	20.62		
R2	18.26		
S	26.2±0.3		
V'	19.5+1.4/-0		
W'	2.1/3.65		
Z'	32 Max		
VV THREAD	M15x1-6g		

Delivered W/O Contacts

CONTACT LAYOUT : 11-22

CONTACT TYPE : SOCKET(500 Matings)

Е

ORIENTATION : C

SOURIAU shall not be liable for due to a use of the Products the Specifications issued by either (professional recommend



ω		А	
			4
AS EXAMPLE	3		3
	mity or damage		
which does no er of the Parties adation, technic	comply with or by a third party al notice.)		
Intry Ju FR	risdiction & Contro Not Listed	I List	2
1J22SCL			
		MOD N°	
site Recept	CUSTOMER D acle 8D series		_
ar :	NPRDS / PI 859		- 1
I.COM	COM This document is the property of SOURIAU it must not be reproduced or communicated without permission		
		SHEET	
J22SCL-C		1/2	
_		-	

,						
4	/	Contact Layout			Т	Panel Cur SQUARE FLANGE RECEPTACLE (TYPE 0) REAR MOUNTING
		4#22D]		R 1	
ω	Ctc A B C D	X Y 1.905 1.905 1.905 -1.905 -1.905 -1.905 -1.905 1.905	-			Dim ØA ØAA R1 ØT
	+					SOURIAU shall not be liable for due to a use of the Products the Specifications issued by either
CJ						(professional recommend Court F PN: 8D011
					A 06-10-2 ISS DAT Designed By: TITLE	2016 First Release E Latest modification - by Date: Composition
_					SCALE NA SOURIA	General linear Tolerances:
	Н	G	F	E	FORMAT A3 D	SOURIA 8D011

Т

ш

т

G

0

