ſ	т р т	m		0	Φ	Þ	
4	Z						4
ယ				LAYOUT SHOWN AS EX	AMPLE		3
	Keying Sho	wn as example					
	CHARACTERISTICS	Connector dimension					
$ \longrightarrow $		Dim Nominal ØS 25 Max					
2	-Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed				
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			FR Not Listed 2 PN: 8D511Z99SD 2			
	-Temperature Range _: -65°C to +175°C		A 20-10-2016	First Release			
	-Salt Spray : 500 hours		ISS DATE			MOD N°	19
	-Mass : 18.09 g ± 10%		Designed By:	Latest modification - by Date:	CUSTO	MOD N	_
		TITLE Aluminium Plug 8D series				es	
<u> </u>	BASIC SERIES: 8D 5 - 11 Z 99 S D SHELL TYPE : Plug with RFI Shielding - 11 Z 99 S D		SCALE -	General linear Tolerances:	NPF	DS / PROJECT 859	
	CONTACT TYPE : Standard Crimp Contact		- SOURIAU	WWW.SOURIAU.COM SOURIAU it must not be reproduced		t must not be reproduced or	
	SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings)		—			nmunicated without permission SHEET	
	PLATING : Z = Black Zinc Nickel	CONTACT LAYOUT : 11	A3	SOURIAU 8D511Z9		1/2	
1			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	8D21177	マンリノーし	<u> </u>	

_	т	۵	н т	m		O
		Contact Layout				
4	-x	$ \begin{array}{c} & & & \\ & & & \\ & & & \\ & & $				
	Conta positio ID A B C C D E E F G	X-axis (mm) Y-axis (mm) +.065 (1.65) +.113 (2.87) +.130 (3.30) +.000 (0.00) +.065 (1.65) 113 (2.87) 065 (1.65) 113 (2.87) 030 (3.30) +.000 (0.00) 065 (1.65) +.113 (2.87) 030 (0.00) +.000 (0.00)	1			
ω	Shell Arrangement Numbs size no. conta 11 -99 7	contacts rating location				
	-					SOURIAU shall not be liable for any due to a use of the Products wh
N						the Specifications issued by either of (professional recommendat Countr FR PN: 8D5112
					A 20-10-20 ISS DATE Designed By:	016 First Release
<u> </u>					TITLE SCALE NA	Alumin General linear Tolerances: ±
					SOURIA	
					FORMAT A3	SOURIAU 8D511Z9
	Н	G	F	E	D	C

