# 9001KT1L9 PILOT LIGHT 120VAC 30MM TYPE K +OPTIONS

ľ	VI	а	ı	r

Bezel material	Chromium plated metal
Device short name	K
Enclosure type	Dust and oil resistant weatherproof enclosure indoor/outdoor
Lens type	Domed plastic
Mounting diameter	1.18 in (30 mm)

### Complementary

Cap/operator or lens colour	Blue	
Electrical Connection	Screw clamp terminal	
Light block supply	Via transformer 110 V AC 50/60 Hz Via transformer 120 V AC 50/60 Hz	
Operating Mode	Push-to-test	
Shape	Round head	

#### Environment

NEMA Degree of Protection	NEMA 1/2/3/3R/4/6/12/13
Product Certifications	CSA LR24590 class 3211 03 UL listed file E42259 CCN NKCR CE

### Ordering and shipping details

Category	21426-9001 K (NOT KA,KM,KX)	
Discount Schedule	CS1	
GTIN	785901858065	
Nbr. of units in pkg.	1	
Package weight(Lbs)	6.40 oz (181.437 g)	
Returnability	No	
Country of origin	MX	

### **Packing Units**

Unit Type of Package 1	PCE	
Package 1 Height	5.08 in (12.903 cm)	
Package 1 width	2.00 in (5.08 cm)	
Package 1 Length	12.90 in (32.774 cm)	

## Offer Sustainability

Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

18 months