

Datasheet

mSATA mini 3IE3 series

- SATA 6Gb/s interface
- Exclusive iSLC FW architecture
- iSMART disk health monitoring
- Intelligent error recovery system
- Excellent data transfer speed
- Zero mechanical interference
- Anti-vibration mechanical design
- JEDEC standard MO-300 dimension



Introduction

Innodisk mSATA mini 3IE3 is designed with mSATA mini form factor by MO-300/MO-300B which established by JEDEC, and support SATA III standard (6.0Gb/s) with excellent performance. Regarding of mechanical interference, Innodisk mSATA mini 3IE3 absolutely replaces the traditional hard disk and makes personal computer, in any field, smaller and easier.


Innodisk mSATA mini 3IE3 effectively reduces the booting time of operation system and the power consumption is less than hard disk drive (HDD), and complies with ATA protocol, no additional drives are required, and can be configured as a boot device or data storage device.

mSATA mini 3IE3 series

Contact us for more information
about the mSATA mini 3IE3.

Innodisk is a service-driven provider of industrial embedded flash storage products and technologies, with a focus on the cloud computing, industrial/embedded, and aerospace and defense industries.

Diagram



Specifications

Headquarters (Taiwan)

5F., No. 237, Sec. 1, Datong Rd.,
Xizhi Dist., New Taipei City 221,
Taiwan (R.O.C.)
Tel: +886-2-77033000
Email: sales@Innodisk.com

Branch Offices:

USA
usasales@Innodisk.com
+1-510-770-9421
Europe
eusales@Innodisk.com
+31-(0)40-282-1818
Japan
jpsales@Innodisk.com
+81-3-6667-0161
China
sales_cn@Innodisk.com
+86-755-21673689
www.Innodisk.com

© 2015 Innodisk Corporation.
All right reserved. Specifications
are subject to change without
prior notice.

Interface	SATA III
Flash Type	iSLC
Capacity	8GB~64GB
Max. Channels	2
Sequential R/W (MB/sec, max.)	230/170
Max. Power Consumption	0.6 W (3.3V x 190 mA)
Thermal Sensor	WT as default, ST by option
External DRAM buffer	-
Trim	✓
ATA Security	✓
S.M.A.R.T.	✓
Dimension (WxLxH)	29.85 X 26.8 X 3.7 mm
Environment	Vibration: 20G @7~2000Hz Shock: 1500G @ 0.5ms Storage Temperature: -55°C ~ +95°C MTBF: 3 million hours

Ordering Information

20160307

Operation Temp.	08GB	16GB	32GB	64GB
Standard Grade (0°C ~ +70°C)	DHMSM-08GD09BC1SC	DHMSM-16GD09BC1DC	DHMSM-32GD09BC1DC	DHMSM-64GD09BC1DC
Industrial Grade (-40°C ~ +85°C)	DHMSM-08GD09BW1SC	DHMSM-16GD09BW1DC	DHMSM-32GD09BW1DC	DHMSM-64GD09BW1DC