

PDU Power Cord, C13 to C14 - 10A, 250V, 18 AWG, 6 ft. (1.83 m), Green

MODEL NUMBER: P004-006-AGN











Computer power extension cord connects 2 devices with C13/C14 power connectors or extends your existing power connection by 6 ft.

Features

C14-to-C13 Power Cable Connects Computers, Printers, Servers and Other EquipmentThis IEC-320-C14 to IEC-320-C13 cable is designed for small data center, office workstation and other lower-amp applications. This C14 male to C13 female cord can be used to power a computer, server or monitor; attach a server or drive to a UPS system or PDU; or extend an existing connection up to 6-ft. (1.83 m). The 6-ft. (1.83 m) length allows you flexibility in placing equipment with respect to the power outlet.

Color-Coded to Avoid Misidentification That Can Cause Costly DowntimeThis computer power extension cord features a green SJT jacket and fully molded green ends. The color-coding allows easy, fast identification in a crowded rack or workstation and helps prevent the cable from becoming inadvertently disconnected.

Highlights

- Recommended for powering computers, printers and other essential peripherals
- Adds 6-ft. (1.83 m) to your existing connection to provide more flexibility in placing devices
- C13-to-C14 PDU-style extension cord is ideal replacement for worn-out or missing cable
- Color-coded green for fast, easy identification in a crowded rack or workstation

Applications

- Connect devices like computers, servers and monitors to a PDU up to 6-ft. (1.83 m) away in your data center
- Extend an existing power connection up to 6-ft. (1.83 m) to more easily place a device or reach a power source away from your workstation
- Provide a high-quality replacement for a worn-out or missing power cord

Package Includes

 P004-006-AGN C14 Male to C13 Female Power Cable, 6-ft. (1.83 m), Green

Specifications

OVERVIEW		
UPC Code	037332198907	
Device Compatibility	Computer; Monitor/HDTV; Printer; Server; UPS; PDU	
Country/Region	Global	
INPUT		
Maximum Input Amps	10	
Voltage Compatibility (VAC)	100-250	
PHYSICAL		



Product Compliance	RoHS; REACH	
Product Certifications	CSA (Canada); cUL Listed; UL Listed	
STANDARDS & COMPLIANCE		
Coiled Power Cord	No	
Locking Plug	No .	
High Voltage	Yes	
Angled Plug	No .	
Antibacterial	No .	
FEATURES & SPECIFICATIONS		
Side B - Connector 1	IEC-320-C13	
Side A - Connector 1	IEC-320-C14	
CONNECTIONS		
Storage Humidity Range	20% to 80% RH	
Operating Humidity Range	20% to 80% RH	
Storage Temperature Range	-4° to 140°F (-20° to 60°C)	
Operating Temperature Range	-4° to 140°F (-20° to 60°C)	
ENVIRONMENTAL		
Shipping Weight (kg)	0.23	
Shipping Weight (lbs.)	0.51	
Shipping Dimensions (hwd / cm)	25.15 x 17.78 x 1.27	
Shipping Dimensions (hwd / in.)	9.90 x 7.00 x 0.50	
Cable Length (cm)	182.88	
Cable Length (m)	1.83	
Cable Length (ft.)	6	
Wire Gauge (OD - mm²)	0.82	
Wire Gauge (AWG)	18	
Number of Conductors	3	
Cable Outer Diameter (OD)	7.7mm	
Power Cord Jacket Type	SJT	
Cable Jacket Rating	FT2	
Cable Jacket Material	PVC	
Cable Jacket Color	Green	
Plug Color	Green	



VARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.