

LAURA-O-PG

~40° x 12° oval beam. Assembly with white holder and location pins.

TECHNICAL SPECIFICATIONS:

Dimensions	21.6 mm
Height	13.1 mm
Fastening	glue, pin
ROHS compliant	yes ⓘ


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
LAURA-O	Single lens	PMMA		
LAURA-HLD-PIN	Holder	PC		



ORDERING INFORMATION:


Component		Qty in box	MOQ	MPQ	Box weight (kg)
CP12635_LAURA-O-PG	Single lens	1960	294	98	10.8
» Box size: 480 x 280 x 300 mm					




PHOTOMETRIC DATA (MEASURED):




LED XP-G
 FWHM 44.0 + 15.0°
 Efficiency 91 %
 Peak intensity 4.200 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED XT-E
 FWHM 38.0 + 16.0°
 Efficiency 89 %
 Peak intensity 3.900 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED LUXEON A
 FWHM 36.0 + 15.0°
 Efficiency 92 %
 Peak intensity 3.900 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





LED LUXEON Rebel
 FWHM 41.0 + 12.0°
 Efficiency 90 %
 Peak intensity 5.000 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:


PHOTOMETRIC DATA (MEASURED):



LED NVSxx19A
FWHM 37.0 + 15.0°
Efficiency 89 %
Peak intensity 3.500 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED OSOLON Square EC
FWHM 40.0 + 14.0°
Efficiency 87 %
Peak intensity 3.700 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (SIMULATED):




LED XP-E
 FWHM 60.0 + 10.0°
 Efficiency 91 %
 Peak intensity 3.534 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED NCSxx19A
 FWHM 64.0 + 10.0°
 Efficiency 90 %
 Peak intensity 3.193 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OSRAM Opto Semiconductors
 LED OSLON SSL 150
 FWHM 62.0 + 10.0°
 Efficiency 92 %
 Peak intensity 3.583 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OSRAM Opto Semiconductors
 LED OSLON SSL 80
 FWHM 62.0 + 10.0°
 Efficiency 91 %
 Peak intensity 3.206 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)