Product data sheet Characteristics

XGSZ09L10

Radio frequency identification XG, pre wired M12 female connector, cable 10 m, IP67



Main	
Range of Product	Telemecanique Radio frequency identification XG
Accessory / separate part category	Connection accessories
Accessory / Separate Part Type	Connecting cable
Accessory / separate part designation	Pre-wired M12 female connector
Accessory / separate part destination	For 24 V DC supply of connection box
Cable length	32.81 ft (10 m)

Com	plem	entary

Product Compatibility	XGSZ33ETH TCSAMT31FP	
Electrical connection	1 female connector M12 4 pins A coding	
Color	Black	
Net Weight	1.15 lb(US) (0.52 kg)	

Environment

IP Degree of Protection	IP67
-------------------------	------

Ordering and shipping details

22491-SENS,IDENTIFICATION DEVICE (XGK)	
DS2	
3389118314023	
1	
12.10 oz (343.0 g)	
No	
PL	
	DS2 3389118314023 1 12.10 oz (343.0 g) No

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	1.57 in (4 cm)	
Package 1 width	7.09 in (18 cm)	
Package 1 Length	7.09 in (18 cm)	
Unit Type of Package 2	S02	
Number of Units in Package 2	10	
Package 2 Weight	8.40 lb(US) (3.812 kg)	
Package 2 Height	5.91 in (15 cm)	
Package 2 width	11.81 in (30 cm)	
Package 2 Length	15.75 in (40 cm)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	€Yes	

Contractual warranty

Warranty	18 months

Product data sheet Connections and Schema

XGSZ09L10

Wiring Diagram

Modbus Connections



Pin no.		Signal
1	Red	+ 24 VDC
2	NC	-
3	Black	0 VDC
4	NC	-