REVISIONS DESCRIPTION APPROVED LTR DATE NOTES: UNLESS OTHERWISE SPECIFIED 1. P/N: 40 PROBE HOUSING: MOLDED NYLON. AVAILABLE IN BLACK OR RED CONTACT: NICKEL PLATED BRASS. TUBING: CLEAR ACRYLIC ADAPTER: ANODIZED ALUMINUM. AVAILABLE IN BLACK OR RED 2. P/N: 9214COLOR HOUSING: MOLDED ACETAL. AVAILABLE IN BLK & RED FRAME: NICKEL PLATED BRASS. CONTACT: NICKEL PLATED BeCu OR PHOSPHOR BRONZE. 3. P/N: W-600/COLOR18AWG TINNED COPPER 0.144 [3.66] O.D. PVC INSULATION AVAILABLE IN TEN COLORS. 4. PERFORMANCE: MAXIMUM CURRENT: 4.0 AMPS MAXIMUM VOLTAGE: HANDHELD: 33VAC/60VDC HANDS FREE: 3500 VRMS MAXIMUM TEMPERATURE: 176°F (80°C) 30.0 [762.00] 1.596 [40.55] WHEN ASSEMBLED 0.31 [7.78] — 0.080 [2.03] **—** 0.175 [4.45] 0.375 [9.53] ZEXPOSED LENGTHZ CONTRACT NO. UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES E-Z-HOOK DIVISION OF TEKTEST INC. ARCADIA, CA 91006 U.S.A. 1.312 [33.33] TOLERANCES ARE: FRACTIONS DECIMALS ANGLES DATE APPROVALS ±N/A  $.XX \pm N/A \pm N/A$ DRAWN DESCRIPTION 8/18 R.L.  $A \times \dot{N} \pm \dot{N} / A$ HANDLE PROBE TO STD BANANA PLUG **→** 1.81 [45.97] **→** APPROVED BY MATERIAL SEE NOTES SIZE CODE IDENT NO. DRAWING NO. FINISH REV. SEE NOTES B | **08505** | BX640

DO NOT SCALE DRAWING

SCALE

SHEET 1 OF

USED ON

APPLICATION

**NEXT ASSY**