

# SAFETY DATA SHEET

# Stereze 70% Isopropyl Alcohol, Presaturated Wipes 800ct

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification			
Product identifier			
Product name	Stereze 70% Isopropyl Alcohol, Presaturated Wipes 800ct		
Product number	STIA800W, STIA800RW		
Recommended use of the che	emical and restrictions on use		
Application	Cleaning agent.		
Uses advised against	No specific uses advised against are identified.		
Details of the supplier of the safety data sheet			
Supplier	MicroCare LLC Tel: +1 860-827-0626		
Manufacturer	MICROCARE LLC 595 John Downey Drive New Britain, CT 06051 United States of America CAGE: OATV9 Tel: + 1 800 638 0125, +1 860-827-0626 techsupport@microcare.com		
Emergency telephone number			
Emergency telephone	CHEMTREC 1-800-424-9300 (within the U.S.) +1 703-741-5970 (from anywhere in the world)		
2. Hazard(s) identification			
Classification of the substance	e or mixture		
OSHA Regulatory Status	This Product is Hazardous under the OSHA Hazard Communication Standard.		
Physical hazards	Flam. Liq. 2 - H225		
Health hazards	Eye Irrit. 2A - H319 STOT SE 3 - H336		
Environmental hazards	Not Classified		
Label elements			
Hazard symbols			
Signal word	Danger		
Hazard statements	H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation.		

70%

30%

# Stereze 70% Isopropyl Alcohol, Presaturated Wipes 800ct

Precautionary statements	<ul> <li>P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.</li> <li>P261 Avoid breathing vapor/ spray.</li> <li>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</li> <li>P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove conta lenses, if present and easy to do. Continue rinsing.</li> <li>P337+P313 If eye irritation persists: Get medical advice/ attention.</li> <li>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</li> </ul>	
Supplemental label information	EUH210 Safety data sheet available on request. RCH001a For use in industrial installations only.	
Contains	PROPAN-2-OL	

# Other hazards

This product does not contain any substances classified as PBT or vPvB.

## 3. Composition/information on ingredients

#### Mixtures

### **PROPAN-2-OL**

CAS number: 67-63-0

### Classification

Flam. Liq. 2 - H225 Eye Irrit. 2A - H319 STOT SE 3 - H336

## D.I. WATER

CAS number: 7732-18-5

## Classification

Not Classified

The full text for all hazard statements is displayed in Section 16.

Composition commentsTSCA: The ingredients of this product are on the TSCA Inventory. The exact percentage<br/>(concentration) of composition has been withheld as a trade secret in accordance with<br/>paragraph (i) of CFR 1900.1200

Composition

4. First-aid measures		
Description of first aid measures		
General information	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.	
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention. Place unconscious person on their side in the recovery position and ensure breathing can take place.	

Ingestion	Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Never give anything by mouth to an unconscious person. Place unconscious person on their side in the recovery position and ensure breathing can take place. Keep affected person under observation. Get medical attention if symptoms are severe or persist.		
Skin Contact	Rinse with water.		
Eye contact	Rinse with water. Do not rub eye. Remove any contact lenses and open eyelids wide apart. Get medical attention if any discomfort continues.		
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.		
Most important symptoms and	effects, both acute and delayed		
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.		
Inhalation	A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.		
Ingestion	No specific symptoms known.		
Skin contact	No specific symptoms known.		
Eye contact	Irritating to eyes.		
Indication of immediate medical attention and special treatment needed			
Notes for the doctor	Treat symptomatically.		
5. Fire-fighting measures			
Extinguishing media			
Extinguishing media Suitable extinguishing media	The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.		
Suitable extinguishing media	or water fog. Use fire-extinguishing media suitable for the surrounding fire. Do not use water jet as an extinguisher, as this will spread the fire.		
Suitable extinguishing media Unsuitable extinguishing media	or water fog. Use fire-extinguishing media suitable for the surrounding fire. Do not use water jet as an extinguisher, as this will spread the fire.		
Suitable extinguishing media Unsuitable extinguishing media Special hazards arising from t	or water fog. Use fire-extinguishing media suitable for the surrounding fire. Do not use water jet as an extinguisher, as this will spread the fire. <b>he substance or mixture</b> Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapors may be ignited by a spark, a hot surface or an ember. Vapors may form explosive mixtures with air. Fire-water run-off in sewers may create fire or		
Suitable extinguishing media Unsuitable extinguishing media <u>Special hazards arising from t</u> Specific hazards Hazardous combustion	or water fog. Use fire-extinguishing media suitable for the surrounding fire. Do not use water jet as an extinguisher, as this will spread the fire. <b>he substance or mixture</b> Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapors may be ignited by a spark, a hot surface or an ember. Vapors may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard. Thermal decomposition or combustion products may include the following substances:		
Suitable extinguishing media Unsuitable extinguishing media <u>Special hazards arising from t</u> Specific hazards Hazardous combustion products	or water fog. Use fire-extinguishing media suitable for the surrounding fire. Do not use water jet as an extinguisher, as this will spread the fire. <b>he substance or mixture</b> Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapors may be ignited by a spark, a hot surface or an ember. Vapors may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard. Thermal decomposition or combustion products may include the following substances:		

6. Accidental release measure	15		
Personal precautions, protective equipment and emergency procedures			
Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated. Avoid inhalation of vapors and spray/mists. Use suitable respiratory protection if ventilation is inadequate.		
Environmental precautions			
Environmental precautions	Avoid discharge into drains or watercourses or onto the ground.		
Methods and material for containment and cleaning up			
Methods for cleaning up	Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion. Absorb small quantities with paper towels and evaporate in a safe place. Once evaporation is complete, place paper in a suitable waste disposal container and seal securely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. The contaminated absorbent may pose the same hazard as the spilled material. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.		
Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.		
7. Handling and storage			
Precautions for safe handling			
Usage precautions	Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.		
Advice on general occupational hygiene	Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse.		
Conditions for safe storage, in	cluding any incompatibilities		
Storage precautions	Store away from incompatible materials (see Section 10). Keep away from oxidizing materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage.		
Storage class	Flammable liquid storage.		
Specific end uses(s)			
Specific end use(s)	The identified uses for this product are detailed in Section 1.		
Reference to other sections.	Store away from incompatible materials (see Section 10).		

## 8. Exposure controls/Personal protection

### **Control parameters**

#### Occupational exposure limits

## **PROPAN-2-OL**

Long-term exposure limit (8-hour TWA): OSHA 400 ppm 980 mg/m<sup>3</sup> Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 492 mg/m<sup>3</sup> Short-term exposure limit (15-minute): ACGIH 400 ppm 984 mg/m<sup>3</sup> A4

OSHA = Occupational Safety and Health Administration. ACGIH = American Conference of Governmental Industrial Hygienists. A4 = Not Classifiable as a Human Carcinogen.

### Exposure controls

#### **Protective equipment**



Appropriate engineering controls	Provide adequate general and local exhaust ventilation. Ensure the ventilation system is regularly maintained and tested. Good general ventilation should be adequate to control worker exposure to airborne contaminants. Observe any occupational exposure limits for the product or ingredients.	
Eye/face protection	Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full- face respirator may be required instead.	
Hand protection	No specific hand protection recommended.	
Other skin and body protection	Wear appropriate clothing to prevent repeated or prolonged skin contact.	
Hygiene measures	Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.	
Respiratory protection	Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with OSHA 1910.134. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. Half mask and quarter mask respirators with replaceable filter cartridges should comply should comply with OSHA 1910.134.	
Environmental exposure controls	Keep container tightly sealed when not in use.	
9. Physical and chemical pro	operties	

#### Information on basic physical and chemical properties

Appearance	Clear liquid.
Color	Colorless.
Odor	Alcoholic.
Odor threshold	No information available.
рН	No information available.
Melting point	No information available.
Initial boiling point and range	82°C/180°F @ 101.3 kPa

Flash point	12°C/53°F Tag closed cup.		
Evaporation rate	No information available.		
Evaporation factor	No information available.		
Flammability (solid, gas)	No information available.		
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 2.0 %(V) Upper flammable/explosive limit: 12.7 %(V)		
Other flammability	No information available.		
Vapor pressure	5.2 kPa @ 20°C		
Vapor density	1.82		
Relative density	0.87		
Bulk density	No information available.		
Solubility(ies)	Soluble in water.		
Partition coefficient	No information available.		
Auto-ignition temperature	No information available.		
Decomposition Temperature	No information available.		
Viscosity	No information available.		
Explosive properties	No information available.		
Global Warming Potential (GWP)			
Surface tension			
Refractive index	No information available.		
Particle size	Not applicable.		
Molecular weight	Not applicable.		
Volatility	100%		
Saturation concentration	No information available.		
Critical temperature	No information available.		
Volatile organic compound	This product contains a maximum VOC content of 350 g/l. This product contains a maximum VOC content of 70 %.		
Heat of vaporization (at boiling point), cal/g (Btu/lb)			
10. Stability and reactivity			
Reactivity	See the other subsections of this section for further details.		
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.		

**Possibility of hazardous** The following materials may react strongly with the product: Oxidizing agents. **reactions** 

Conditions to avoid	Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented.	
Materials to avoid	Oxidizing materials. Acids - oxidizing.	
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.	

11. Toxicological information

Information on toxicological effects			
Acute toxicity - oral			
Notes (oral LD₅₀)	Based on available data the classification criteria are not met.		
Acute toxicity - dermal			
Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.		
Acute toxicity - inhalation			
Notes (inhalation LC <sub>50</sub> )	Based on available data the classification criteria are not met.		
Skin corrosion/irritation			
Animal data	Based on available data the classification criteria are not met.		
Serious eye damage/irritation			
Serious eye damage/irritation	Causes serious eye irritation.		
Respiratory sensitization			
Respiratory sensitization	Based on available data the classification criteria are not met.		
Skin sensitization			
Skin sensitization	Based on available data the classification criteria are not met.		
Germ cell mutagenicity			
Genotoxicity - in vitro	Based on available data the classification criteria are not met.		
Carcinogenicity			
Carcinogenicity	Based on available data the classification criteria are not met.		
IARC carcinogenicity	Contains a substance which may be potentially carcinogenic. IARC Group 3 Not classifiable as to its carcinogenicity to humans.		
Reproductive toxicity			
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.		
Reproductive toxicity - development	Based on available data the classification criteria are not met.		
Specific target organ toxicity - single exposure			
STOT - single exposure	STOT SE 3 - H336 May cause drowsiness or dizziness.		
Target organs	Central nervous system		
Specific target organ toxicity - repeated exposure			
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.		
Aspiration hazard			
Aspiration hazard	Based on available data the classification criteria are not met.		

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.		
Inhalation	A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.		
Ingestion	No specific symptoms known.		
Skin Contact	No specific symptoms known.		
Eye contact	Irritating to eyes.		
Route of exposure	Ingestion Inhalation Skin and/or eye contact		
Target Organs	Central nervous system		
Toxicological information on ingredients.			
	PROPAN-2-OL		

Acute toxicity - inhalation		
Acute toxicity inhalation (LC₅₀ vapours mg/l)	16,000.0	
ATE inhalation (vapours mg/l)	16,000.0	
Carcinogenicity		
IARC carcinogenicity	IARC Group 3	Not classifiable as to its carcinogenicity to humans.
NTP carcinogenicity	Not listed.	
OSHA Carcinogenicity	Not listed.	

## 12. Ecological information

Ecotoxicity

Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

Toxicity

Based on available data the classification criteria are not met.

# Ecological information on ingredients.

# PROPAN-2-OL

Acute aquatic tox	icity	
Acute toxicity - fis	h	LC₅₀, 96 hours: 9,640 mg/l, Fish
Acute toxicity - ac invertebrates	luatic	EC₅₀, 48 hours: 5102 mg/l, Daphnia magna
Acute toxicity - ac plants	luatic	IC₅₀, 72 hours: >2,000 mg/l, Algae
Persistence and degradability		
Persistence and degradability The degradability of the product is not known.		
Bioaccumulative potential		
<b>Bio-Accumulative Potential</b>	No data	available on bioaccumulation.

Partition coefficient	No information available.			
Ecological information on ingredients.				
PROPAN-2-OL				
Partition coefficie	nt : 0.05			
Mobility in soil				
Mobility	No data available.			
Other adverse effects				
Other adverse effects	None known.			
13. Disposal considerations				
Waste treatment methods				
General information	The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.			
Disposal methods	Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.			
14. Transport information				
General	Requirements for marking and labeling of package varies depending on mode of transport. If uncertain of proper markings and labeling, call MicroCare for assistance.			
Air transport notes	Forbidden for passenger and cargo aircraft.			
UN Number				
UN No. (IMDG)	3175			
UN proper shipping name				
Proper shipping name (TDG)	UN3175, SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Isopropanol), 4.1, PGII			
Proper shipping name (IMDG)	UN3175, SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Isopropanol), 4.1, PGII			
Proper shipping name (ICAO)	Forbidden for passenger and cargo aircraft.			
Proper shipping name (DOT)	UN3175, SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Isopropanol), 4.1, PGII			
Transport hazard class(es)				
IMDG Class	4.1			
Packing group				
IMDG packing group	П			
Environmental hazards				
Environmentally Hazardous Substance No.				

Transport in bulk according to No information required. Not applicable. Annex II of MARPOL 73/78 and the IBC Code

#### 15. Regulatory information

### **US Federal Regulations**

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities None of the ingredients are listed or exempt.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA) None of the ingredients are listed or exempt.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities None of the ingredients are listed or exempt.

### SARA 313 Emission Reporting

None of the ingredients are listed or exempt.

CAA Accidental Release Prevention None of the ingredients are listed or exempt.

**FDA - Essential Chemical** None of the ingredients are listed or exempt.

**FDA - Precursor Chemical** None of the ingredients are listed or exempt.

## SARA (311/312) Hazard Categories

None of the ingredients are listed or exempt.

**OSHA Highly Hazardous Chemicals** None of the ingredients are listed or exempt.

# US State Regulations

# California Proposition 65 Carcinogens and Reproductive Toxins

This product does not contain any chemicals found on the California Proposition 65 Carcinogens and Reproductive Toxins.

## California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed or exempt:

PROPAN-2-OL

California Air Toxics "Hot Spots" (A-II) None of the ingredients are listed or exempt.

# California Directors List of Hazardous Substances

The following ingredients are listed or exempt:

PROPAN-2-OL

## Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

PROPAN-2-OL

## Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

#### PROPAN-2-OL

# Minnesota "Right To Know" List

The following ingredients are listed or exempt:

## PROPAN-2-OL

## New Jersey "Right To Know" List

The following ingredients are listed or exempt:

PROPAN-2-OL

# Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

PROPAN-2-OL

### Inventories

# Canada - DSL/NDSL DSL

US - TSCA All the ingredients are listed or exempt. Present.

# US - TSCA 12(b) Export Notification

Not listed.

16. Other information

Abbreviations and acronyms used in the safety data sheet	TDG: The transport of dangerous goods act
	<ul> <li>IATA: International air transport association.</li> <li>ICAO: Technical instructions for the safe transport of dangerous goods by air.</li> <li>IMDG: International maritime dangerous goods.</li> <li>CAS: Chemical abstracts service.</li> <li>ATE: Acute toxicity estimate.</li> <li>LC<sub>50</sub>: Lethal concentration to 50 % of a test population.</li> <li>LD<sub>50</sub>: Lethal dose to 50% of a test population (median lethal dose).</li> <li>EC<sub>50</sub>: 50% of maximal effective concentration.</li> <li>PBT: Persistent, bioaccumulative and toxic substance.</li> <li>vPvB: Very persistent and very bioaccumulative.</li> </ul>
Classification abbreviations and acronyms	Flam. Liq. = Flammable liquid Eye Irrit. = Eye irritation STOT SE = Specific target organ toxicity-single exposure
Training advice	Only trained personnel should use this material.
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	1/26/2021
Revision	59
Supersedes date	11/25/2020
SDS No.	PRESAT - STIA800
SDS status	Approved.

Hazard statements in full	H225 Highly flammable liquid and vapor.
	H319 Causes serious eye irritation.
	H336 May cause drowsiness or dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.