General ordering data Order No.	0266320000
Part designation	AST 1 6.3 KRG
Version	Special terminal, special connections, 2.5 mm²,
FANI	Flat-blade connection, KrG, Medium yellow, TS 32
EAN	4008190167981
Qty.	50 pc(s).
Product notes	
Note, technical data	Cable-lug connections should be fitted with insulating sleeves. 20 A with F 6.3 or 2 x F 2.8
Additional technical data	
Colour of insulating material	Medium yellow
Connection direction	top
End plate required	Yes
Explosion-tested version "Ex e"	No
Installation advice	TS 32
Insulating material	KrG
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	4
Open sides	right
Operating temperature range	- 60 °C, + 130 °C
Product family	SAK Series
Type of connection	Plugged
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	5VA
Version	Feed-through terminal
CSA rating data	
Voltage (CSA)	300 V
CSA current	16 A
Conductors for clamping (additional	
No. of connections	4
Conductors for clamping (rated connection)	
Clamping range, min.	0.5 mm²
Clamping range, max.	2.5 mm²
Type of connection	Flat-blade connection
Connection direction	top
No. of connections	4
Flexible, min.	0.5 mm²
Flexible, max.	2.5 mm²
Dimensions	
Width	6.5 mm
Height of lowest version	46 mm



Dimensions		
Length	58 mm	
Weight	14.24 g	
TS 32 offset	26 mm	
Other connections		
Cable-lug connection	unslotted	
No of connections	4	

Rated cross-section spade connector 2.8 mm 1 mm<sup>2</sup>
Rated cross-section spade connector 6.3 mm 2.5 mm<sup>2</sup>

Rating data

Rated cross-section

Rated voltage

Rated impulse voltage

Rated current

2.5 mm²

500 V

Rated impulse voltage

6 kV

Standards IEC 60947-7-1 / IEC 61210

Current with max. conductor 20 A Pollution severity 3

Voltage (UL) 600 V Current (UL) 13 A

## Approvals

Approvals institutes



STEP 0266320000\_02717\_AST\_1\_6.3\_KRG\_STP.stp

ETIM 2.0	EC000897	
ETIM 3.0	EC000897	
eClass 4.1	27-14-11-31	
eClass 5.0	27-14-11-31	
eClass 5 1	27-14-11-31	

## Similar products

Order No.		Version
0478220000	AST 1 6.3/2.8 KRG	Special terminal, special connections, 2.5 mm², Flat-blade connection, KrG, Medium yellow, TS 32
0298020000	AST 3 6.3 KRG	Special terminal, special connections, 2.5 mm², Flat-blade connection, KrG, Medium yellow, TS 32
0442420000	AST 3 6.3/2.8 KRG	Special terminal, special connections, 2.5 mm², Flat-blade connection, KrG, Medium yellow, TS 32



0442470000 AST 3 6.3/2.8 KRG/BL

Special terminal, special connections, 2.5 mm², Flat-blade connection, KrG, blue, TS 32

