

HDC enclosures HDC IP68 06B SS 2M32

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com







The new RockStar® enclosures are resistant to seawater and offer a high degree of shock resistance, meet IP 68 and IP 69K, and have been developed for use under extreme environmental conditions and designed for the high vibration requirements acc. to DIN EN 61373 cat. 2 (bogie). As such, this housing family is ideally suited for fault- and maintenance-free operation of heavy-duty connectors in transport and traffic engineering as well as in power engineering and in applications with extreme requirements. During development, measures were also implemented to make the enclosures extremely EMC-resistant.

General ordering data

Order No.	<u>1081220000</u>
Туре	HDC IP68 06B SS 2M32
Version	HDC enclosures, Size: 3, Protection degree: IP 68, Base enclosure, Screw plug, Standard, Size of cable entries: M 32
GTIN (EAN)	4032248877188
Qty.	1 pc(s).



HDC enclosures **HDC IP68 06B SS 2M32**

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold

Germany Fon: +49 5231 14-0

Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Dimensions and weights

Length	156 mm	Width	80 mm
Height	100.5 mm	Mounting dimension - width	127 mm
Mounting dimension - height	60 mm Net weight		845 g
Temperatures			
Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	125 °C
Dimensions			
Takal lan oda la acción o	150	Middle bassains C	00
Total length housing	156 mm	Width housing C	80 mm
Height of housing B	100.5 mm	Hole pitch length A2	127 mm
Cable entry	w. threading		

Housing main material	diecast aluminium

Version

Design of housing	Base enclosure	Size	3
Design	Standard	Top part/bottom part/lid	lower part
Design of locking system	Screw plug	Cable entry	w. threading
Size of cable entries	M 32	Number of cable entry on top	0
Number of cable entry sideways	2		

Classifications

ETIM 2.0	EC000437	ETIM 3.0	EC000437
UNSPSC	30-21-18-01	eClass 4.1	27-14-08-05
eClass 5.1	27-14-34-19	eClass 6.2	27-14-34-19
eClass 7.1	27-44-05-15		

Approvals

Approvals



ROHS	Conform



HDC enclosures HDC IP68 06B SS 2M32

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Drawings

