

The HGS1M Standard Style Heel Grounder provides a conductive sole under the heel, and a stretch-nylon strap around the back of the shoe. This quality grounder features a durable two-layer sole, lot number and 23-inch multi-strand ribbon. Heel Grounders are designed and manufactured for comfort, durability and cost effectiveness.

Properties	Typical Value	Test Method
Hook and Loop	3/4"	
Elastic Strap	Black	
Sole Interior	Non-marking	
Sole Exterior	<10⁵ ohms	
Total Grounder	1.0 x 10 <sup>6</sup> ohms	ANSI/ESD S20.20, EIA 625 ESD-SP9.2

## Item Description

HGS1M Standard Heel Grounder, 1 Megohm Resistor

## UL Listed

Note: This product is not recommended for use on equipment with operating voltage exceeding 250 VAC.

CAUTION: The ESD Series is for electrostatic control. It will not reduce or increase your risk of receiving electric shock when using or working on electrical equipment. Follow the same precautions you would use without wrist straps, including:

• Make certain that equipment having a grounding type plug is properly grounded.

• Make certain that you are not in contact with grounded objects other than through the ESD Series.

Unless otherwise noted, tolerance ± 10% Specifications and procedures subject to change without notice.	HGS1M - HEEL GROUNDER, STANDARD, 1 MEG		
SCS	926 JR Industrial Drive, Sanford, NC 27332	DRAWING	<b>DATE</b>
	WEB SITE: <u>StaticControl.com</u>	NUMBER	August
	PHONE (919) 718-0000	HGS1M	2015

Listing #90P1

24" Conductive Ribbon

© 2015 DESCO INDUSTRIES INC. Employee Owned

Hook and Loop Strap

**Rubber Sole**