# NSYTBP292416HT

PC box IP66 IK08 RAL7035 Int.H275W225D160 Ext.H291W241D168 Transp.cover H60



#### Main

Thalassa
Thalassa TBP
Multi-purpose
Industrial box
11.46 in (291 mm)
9.49 in (241 mm)
6.61 in (168 mm)
10.83 in (275 mm)
8.86 in (225 mm)
6.30 in (160 mm)
Wall mounted
1 body 1 cover 4 cover screw
One piece moulded
High transparent cover
Plastic screws
Captive screw flat outside sealed area
Cover by captive screws

#### Complementary

Material	polycarbonate	
Color	Gray RAL 7035) Transparent	
Standards	UL 508 A IEC 62208	
Product Certifications	TÜV UL	
Electrical Insulation Class	Class II	
Mounting location	Outdoor	
Net Weight	2.95 lb(US) (1.34 kg)	

### Environment

IP degree of protection	IP66 conforming to NEMA 4.4X
IK degree of protection	IK08 IEC 62262
Fire resistance	1760 °F (960 °C)
Ambient Air Temperature for Storage	5140 °F (-1560 °C)
Operating temperature	-13176 °F (-2580 °C)

### Ordering and shipping details

80033-ENCLOSURE SYSTEMS POLYESTER	
ES1	
3606480165917	
1	
2.95 lb(US) (1.34 kg)	
No	
HU	
	ES1 3606480165917 1 2.95 lb(US) (1.34 kg) No

## Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	6.61 in (16.8 cm)	
Package 1 width	9.49 in (24.1 cm)	
Package 1 Length	11.46 in (29.1 cm)	

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	<sup>™</sup> REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

### Contractual warranty

Warranty	18 months