

Specification Sheet

USB2.0 Flash Drive AH112





Apacer Technology Inc.

1F., No. 32, Zhongcheng Rd., Tucheng Dist., New Taipei City 236, Taiwan Tel: +886-2-2267-8000 Fax: +886-2-2267-2261 www.apacer.com



Table of Contents

| 1. Product Introduction | 3 |
|-------------------------|---|
| 2. Product Features | |
| 3. Specifications | |
| 4. Physical Dimension | |
| 5. Revision History | |



1. Product Introduction

Reducing the body to the limit, AH112 applies composite metal material to set an overall sense of technology, after that carving hollowed-out geometric pattern in the square shape and use asymmetric dynamic to symbolize rapid data transmission. Each line is extremely concise without redundancy.

The hollowed-out geometric pattern of AH112 USB flash drive can be used as strap holes as well. Going with metal beads, they can be hung on handbags, key chains or mobile phone straps, giving consideration to both chic and practicability. Compact metal finish USB drive can be an accessory in the delicate texture of the wallet, in this way it reveals urban minimalist style and simple beauty inherent in a low profile design aesthetics.

When connecting with laptops or computers, there is only 1.3 cm of length in sight and it's a perfect match for Ultrabook emphasizing lightness and neatness!

2. Product Features


- High-speed USB 2.0 certified, backwards compatible with USB 1.1
- USB powered. No external power required.
- Compact and slim with only 2.4cm in length
- Stylish and compact
- Capless design
- Trendy accessory with delicate metal bead chain attached
- Advanced COB technology with water-proof, dust-proof and shock-proof functions
- RoHS compliant



3. Specifications

| Specifications | |
|-----------------------|---|
| Interface | High-speed USB 2.0 certified, backwards compatible with USB 1.1 |
| Power supply | USB bus powered; No external power required |
| Operating Systems | Windows 8/7/Vista/XP, Mac OS 10.4 and Linux 2.6.33 or |
| Supported | above |
| Capacity | 4GB-32GB |
| Operating Temperature | 0° C to +60° C (32° F to 140° F) |
| Storage Temperature | -20° C to +60° C (-4° F to +140° F) |
| Dimensions | 24.3 x(W)12x(H)4.5mm |
| Weight | 2.5g (metal chain is not included) |
| Certificate | CE, FCC, BSMI |

4. Physical Dimension



Unit: mm



5. Revision History

| Revision | History | Date | Remark |
|----------|------------------|---------------|--------|
| 1.0 | Official release | March 04,2015 | |