

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)

Aluminum die-cast sleeve housing, with grommet, locking screws with knurled head, for a metric M32 cable gland, angled cable outlet, type VC4



Product Features

- ☑ Housing with two cable entries is available
- Manageria Angled cable outlet so the cable can be routed as desired, from the side and straight
- Main Aluminum housing with extended cabling space for high-position and power contact inserts



Key commercial data

| Packing unit | 1 PCE |
|--------------------------------------|-----------|
| Weight per Piece (excluding packing) | 313.5 GRM |
| Custom tariff number | 85369010 |
| Country of origin | Poland |

Technical data

Dimensions

| Height | 90 mm | |
|-----------------------------------|---|--|
| Ambient conditions | | |
| Ambient temperature (operation) | -40 °C 125 °C | |
| General | | |
| Note | When using fiber optics, the bending radii of the cable manufacturers must be observed. | |
| Design | VC4 | |
| Color | gray aluminum | |
| Locking type | Screw locking, knurled head | |
| Tightening torque, mounting screw | 1.5 Nm ± 0.3 Nm | |
| Fixing screws | M4 | |



Technical data

General

| No. of cable exits | 1 |
|---|---------------------|
| Cable exit | Angled |
| Screw connection | None |
| Type of the screw connection | M32 x 1.5 |
| Housing material | Aluminum die-cast |
| Seal material | NBR, conductive |
| Material of locking screw | Nickel-plated brass |
| Inflammability class according to UL 94 | V0 |

Classifications

eCl@ss

| eCl@ss 4.0 | 272607xx |
|------------|----------|
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27143424 |
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27371205 |
| eCl@ss 7.0 | 27371205 |
| eCl@ss 8.0 | 27371205 |

ETIM

| ETIM 3.0 | EC000437 |
|----------|----------|
| ETIM 4.0 | EC000437 |
| ETIM 5.0 | EC000437 |

UNSPSC

| UNSPSC 6.01 | 31261502 |
|---------------|----------|
| UNSPSC 7.0901 | 31261502 |
| UNSPSC 11 | 31261502 |
| UNSPSC 12.01 | 31261502 |
| UNSPSC 13.2 | 31261502 |

Approvals

Approvals

Approvals

GOST



Approvals

Ex Approvals

Approvals submitted

Approval details



Accessories

Accessories

Device marking

Engraving material - GPE 22X22 SR/R - 0806628



Engraving material, Sheet, silver, Unlabeled, Can be labeled with: Engraving, Plotter, Mounting type: Adhesive, Lettering field: 22 x 22 mm

Full screw connection

Cable gland - HC-M-KV-M32(14-21) - 1690587



Metal screw connection up to 5 bar, thread length: 8 mm, cable diameter: 14 - 21 mm, WAF 34, screw connection: M32

Cable gland - HC-M-KV-M32(19-27) - 1646010



Metal screw connection up to 5 bar, thread length: 8 mm, cable diameter: 19 - 27 mm, WAF 43, screw connection: M32

11/22/13 Page 3 / 4



Accessories

Cable gland - HC-EMV-KV-M32(11-21) - 1690529



EMC screw connection up to 5 bar, thread length: 9 mm, cable diameter: 11.0 - 21.0 mm, WAF 36, screw connection: M32

Drawings



Dimensioned drawing



© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com