Data sheet | Item number: 267-177

Female connector; with direct ground contact; with snap-in mounting feet; 7-pole; 1,00 mm²; white



www.wago.com/267-177





Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.



Item description

- Flexible, modular 5- to 11-pole connector system
- Future system expansions possible
- Compact design

Data Electrical data

Ratings per IEC/EN

Ratings per	IEC/EN 60664-1	
Rated voltage (III/2)	500 V	
Rated impulse voltage (III/2)	4 kV	
Rated current	6 A	
Legend (ratings)	(III / 2) ≙ Overvoltage category III / Pollution degree 2	

Connection data

Number of connection types 1	
------------------------------	--

Connection 1

Connection technology	PUSH WIRE [®]
Strip length	8 mm / 0.31 inches
Pole number	7

Physical data

Width	26 mm / 1.024 inches
Height from the surface	34 mm / 1.339 inches
Depth	42 mm / 1.654 inches

Material Data

Note (material data)

Information on material specifications can be found here

Color	white
Material group	

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG	Do you have any questions about our products?
Hansastr. 27	We are always happy to take your call at +49 (571) 887-44222.
32423 Minden	
Phone: +49571 887-0 Fax: +49571 887-169	
Email: info.de@wago.com Web: www.wago.com	

Data sheet | Item number: 267-177

www.wago.com/267-177



Insulation m	aterial	Polyamide (PA66)	
Flammability	y class per UL94	VO	
Clamping sp	oring material	Chrome-nickel spring steel (CrNi)	
Contact material		Electrolytic copper (E _{Cu})	
Contact pla	ting	Tin	
Fire load		0.591 MJ	
Weight		13 g	
Environme	ntal requirements		
Temperatur	e stability	105 °C	
Commercia	al data		
Product Gro	pup	8 (Misc. Chassis Mount Blocks)	
eCl@ss 10.0)	27-44-03-14	
eCl@ss 9.0		27-44-03-14	
ETIM 8.0		EC000458	
ETIM 7.0		EC000458	
PU (SPU)		500 pcs	
Packaging t	уре	bag	
Country of a	prigin	PL	
GTIN		4044918499835	
Customs ta	riff number	85366990990	
	ntal Product Compliance		
Rohs Comp	pliance Status	Compliant,No Exemption	
Approvals	/ Certificates		
General appr	ovals		
Logo	Approval	Additional Approval Text	Certificate name
	CCA DEKRA Certification B.V.	EN 61984	NL-47718
KEMA	KEMA/KEUR DEKRA Certification B.V.	EN 61984	71- 100641
	UL	UL 1977	E45171

UL International Germany GmbH

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222. 

VDE		EN 61984		40032309
	Zertifizierungsinstitut	EN 01964		40032309
Deverte etc				
Downloads Documentation				
Additional Information				
Technical Section Technical explanations		2019 Apr 3	pdf 2.0 MB	Download
CAD/CAE-Data				
CAD data				
2D/3D Models 267-177			URL	Download
CAE data				
ZUKEN Portal 267-177			URL	Download
EPLAN Data Portal 267-177			URL	Download
Environmental Product Co	ompliance			
Compliance Search				
Environmental Product Compli	ance 267-177		URL	Download
Female connector; with direct of 1,00 mm²; white	ground contact; with snap-in mount	ing feet; 7-pole;		

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.