Product data sheet Characteristics

9001K3L1YH13 PUSH BUTTON 600VAC 10A 30MM T-K





Main

Range of Product	Harmony 9001K
Product or Component Type	Illuminated push-button
Device short name	К
Type of operator	Spring return
Operator profile	Yellow flush
Operator additional information	Extended metallic guard

Complementary

Bezel material	Chromium plated metal
Mounting diameter	1.18 in (30 mm)
Shape of signaling unit head	Round
Light source	incandescent
Light source	Without
Bulb base	BA 9s
Light block supply	Via integral transformer
[Us] rated supply voltage	110120 V AC 50/60 Hz
Contacts type and composition	1 C/O
Connections - terminals	Screw clamp terminals
Operating position	Any position
[le] rated operational current	10 A, AC-15
	10 A, DC-13
Contact operation	Standard
Device presentation	Complete product

Environment

Product Certifications	NEMA CSA LR24590 class 3211 03 CE UL listed file E42259 CCN NKCR
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13

Ordering and shipping details

Category	21426 - 9001 K (NOT KA,KM,KX)	
Discount Schedule	CS1	
GTIN	785901726777	
Nbr. of units in pkg.	1	
Package weight(Lbs)	8.00 oz (226.796 g)	
Returnability	No	
Country of origin	MX	

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.08 in (12.903 cm)
Package 1 width	2.00 in (5.08 cm)
Package 1 Length	12.90 in (32.774 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☐ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months