

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 (818) 701-4939 Fax:

### **GBJL10005 THRU GBJL1010**

## **10 Amp Bridge Rectifier**

## **Glass Passivated** 50 to 1000 Volts

# **GBJL** 0

DIMENSIONS						
	INCHES		MM			
DIM	MIN	MAX	MIN	MAX	NOTE	
Α	1.067	1.091	27.10	27.70		
В	.551	.575	14.00	14.60		
С	.570	.610	14.50	15.50		
D	.071 typ		1.80 typ			
Е	.339	.354	8.60	9.00		
F	.071	.087	1.80	2.20		
G	.120	.134	3.00	3.40		
Н	.110	.126	2.80	3.20		
J	.098	.114	2.50	2.90		
K	.012	.028	0.30	0.70		
L	.098	.114	2.50	2.90		
М	.035	.043	0.90	1.10		
N	.390	.400	9.80	10.20		
0	.290	.300	7.30	7.70		
Р	.079	.094	2.00	2.40		
R	.150	.157	3.60	4.00		
Case Type						

#### **Features**

- Halogen free available upon request by adding suffix "-HF" Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Low forward voltage drop, high current capability.
- Ideal for printed circuit board
- Lead Free Finish/RoHS Compliant (NOTE 1)("P" Suffix designates RoHS Compliant. See ordering information)

- UL Recognized File # E165989
- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Mounting Torque: 5in-lbs.

MCC	Device	Maximum	Maximum	Maximum
Catalog	Marking	Reccurrent	RMS	DC
Number		Peak Reverse	Voltage	Blocking
		Voltage	_	Voltage
GBJL10005	GBJL10005	50V	35V	50V
GBJL1001	GBJL1001	100V	70V	100V
GBJL1002	GBJL1002	200V	140V	200V
GBJL1004	GBJL1004	400V	280V	400V
GBJL1006	GBJL1006	600V	420V	600V
GBJL1008	GBJL1008	800V	560V	800V
GBJL1010	GBJL1010	1000V	700V	1000V


#### Electrical Characteristics @ 25°C Unless Otherwise Specified


Average Forward Current	$I_{F(AV)}$	10 A	Tc = 110°C
Peak Forward Surge	I <sub>FSM</sub>	170A	8.3ms, half sine
Current Maximum			
Instantaneous Forward Voltage	$V_{F}$	1.05V	I <sub>FM</sub> =5.0A T <sub>J</sub> = 25°C
Maximum DC Reverse Current At Rated DC Blocking Voltage	I <sub>R</sub>	10 μA 500uA	T <sub>J</sub> = 25°C T <sub>J</sub> = 125°C
Typical thermal	R <sub>⊙JA</sub>	22°C/W	Units mounted on PCB without heatsink
resistance	$R_{\Theta JC}$	1.4°C/W	Unit case mounted on Al plate heatsink
Typical Junction Capacitance	CJ	55 pF	Measured at 1.0MHz, V <sub>R</sub> =4.0V


1. High Temperature Solder Exemption Applied, see EU Directive Annex Notes 7 Notes:


2. Pulse Test: Pulse Width 300usec, Duty Cycle 1%


Micro Commercial Components













#### **Ordering Information:**

Device	Packing
Part Number-BP	Bulk: 2.2K/Ctn

Note: Adding "-HF" suffix for halogen free, eg. Part Number-BP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.