Product data sheet Characteristics

NSYSMX18840

SMX 304L stainless monobloc enclosure, H1800xW800xD400mm, Scotch Brite® finish.





Main	
Range	Spacial
Product name	Spacial SMX
Enclosure type	Multi-purpose
Category	Compact enclosure
Nominal height	70.87 in (1800 mm)
Nominal width	31.50 in (800 mm)
Nominal depth	15.75 in (400 mm)
Product installation	Floor-standing
Device composition	1 body 1 cable gland plate 1 locking system with handle door 4 mounting plate bracket 1 door

Complementary

Body type	Single piece body folded and welded	
Door type	Solid	
Door opening side	Reversible 120 °)	
Number of doors	Front face 1	
Lock type	3 points lock, handle with 5 mm double-bar insert	
Type of gland plate	Plain	
Accessibility for operation	Front	
Mounting plate description	Without mounting plate	
Material	Body and door stainless steel 304L Handle zamak Hinge stainless steel	
Removable parts	Door by hinges Mounting plate bracket by screws Cable gland plate by clips	
Surface finish	Enclosure Scotch-Brite® brushed Handle painted	
Net Weight	216.05 lb(US) (98 kg)	

Environment

Littletine		
Standards	IEC 62208	
IP degree of protection	IP66 IEC 60529	
IK degree of protection	IK10 IEC 62262	
Product Certifications	CAN/CSA 22 UL 508	
Environmental characteristic	Corrosive Specific hygiene	

Ordering and shipping details

Category	80035-ENCLOSURE SYSTEMS FLOOR MOUNT
Discount Schedule	ES1
GTIN	3606480155826
Nbr. of units in pkg.	1
Package weight(Lbs)	216.05 lb(US) (98.0 kg)



Returnability	No
Country of origin	BG

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	75.98 in (193 cm)	
Package 1 width	33.46 in (85 cm)	
Package 1 Length	18.90 in (48 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	🗗 Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty

18 months