6GK5004-1BF00-1AB2

Data sheet



SCALANCE XB004-1LD unmanaged Industrial Ethernet Switch for 10/100 Mbit/s; for setting up small star and line topologies; LED diagnostics, IP20, 24 V AC/DC power supply, with 4x 10/100 Mbit/s twisted pair ports with RJ45 sockets; 1 x 100 Mbit/s single-mode glass fiber-optic cable port with SC socket; manual available as a download .

product type designation	SCALANCE XB004-1LD
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
for network components or terminal equipment	4; RJ45
number of 100 Mbit/s SC ports	
 for multimode 	0
for single mode (LD)	1
interfaces / other	
number of electrical connections	
for power supply	1
type of electrical connection	
for power supply	3-pole terminal block
supply voltage, current consumption, power loss	
type of voltage / 1 / of the supply voltage	DC
supply voltage / 1 / rated value	24 V
power loss [W] / 1 / rated value	2.4 W
supply voltage / 1 / rated value	19.2 28.8 V
consumed current / 1 / maximum	0.1 A
 type of electrical connection / 1 / for power supply 	3-pole terminal block
 product component / 1 / fusing at power supply input 	Yes
• fuse protection type / 1 / at input for supply voltage	0.6 A / 60 V
type of voltage / 2 / of the supply voltage	
supply voltage / 2 / rated value	19.2 28.8 V
ambient conditions	
ambient temperature	
 during operation 	-10 +60 °C
during storage	-40 +80 °C
during transport	-40 +80 °C
relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	Box
width	45 mm
height	100 mm
depth	87 mm

SCALANCE XB004-1LD

not weight	0.165 kg	
net weight fastening method	0.165 kg	
35 mm top hat DIN rail mounting	Yes	
wall mounting	Yes	
S7-1500 rail mounting	No	
product functions / management, configuration, engineeri		
product function	No	
multiport mirroringCoS	Yes	
PROFINET conformity class	A	
product function / switch-managed	No	
product functions / redundancy	140	
product function ■ Parallel Redundancy Protocol (PRP)/operation in	Yes	
the PRP-network		
 Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) 	No	
standards, specifications, approvals		
standard		
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4	
 for safety / from CSA and UL 	UL 60950-1, CSA C22.2 No. 60950-1	
 for emitted interference 	EN 61000-6-4 (Class A)	
for interference immunity	EN 61000-6-2	
MTBF	238 y	
reference code		
 according to IEC 81346-2 	KF	
• according to IEC 81346-2:2019	KFE	
standards, specifications, approvals / CE		
certificate of suitability / CE marking	Yes	
standards, specifications, approvals / hazardous environn	nents	
standard / for hazardous zone	EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X	
certificate of suitability		
CCC / for hazardous zone according to GB standard	Yes	
standards, specifications, approvals / other		
certificate of suitability	EN 61000-6-2, EN 61000-6-4	
• C-Tick	Yes	
KC approval	Yes	
further information / internet-Links		
Internet-Link		
 to web page: selection aid TIA Selection Tool 	http://www.siemens.com/tia-selection-tool	
 to website: Industrial communication 	http://www.siemens.com/simatic-net	
to website: Industry Mall	https://mall.industry.siemens.com	
 to website: Information and Download Center 	http://www.siemens.com/industry/infocenter	
• to website: Image database	http://automation.siemens.com/bilddb	
to website: CAx-Download-Manager	http://www.siemens.com/cax	
to website: Industry Online Support	https://support.industry.siemens.com	
security information		
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com.	

(V3.4)

last modified: 2/8/2022 🖸