Product data sheet Characteristics

NSYVDM7U4P Wall rack VDM 7U swi chass D400





Main

Spacial
Spacial VDM
Electronic application
Compact enclosure
1-body
Swing
15.75 in (400 mm)
23.62 in (600 mm)
15.75 in (400 mm)
Wall-mounting
Electronics and networks
1 cable gland plate bottom 2 lock 19" swing rack 1 body 1 door with lock 1 19" swing rack

Complementary

Door type	Glass	
Number of doors	Front face 1	
Door opening side	Reversible 120 °)	
Lock type	3 mm double-bar lock	
Type of gland plate	Standard	
Number of units 19"	7	
Accessibility for operation	Front	
Removable parts	Door by hinges Rack by fixing element	
Material	Enclosure and 19" rack steel	
Surface finish	Enclosure and 19" rack epoxy-polyester powder	
Color	Enclosure and 19" rack Gray RAL 7035)	
Standards	IEC 62208	
Net Weight	41.40 lb(US) (18.78 kg)	
Width	23.62 in (600 mm)	
Height	15.75 in (400 mm)	
Depth	15.75 in (400 mm)	

Environment

IP degree of protection	IP66 IEC 60529
IK degree of protection	IK08 IEC 62262

Ordering and shipping details

Category	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	3606480174513
Nbr. of units in pkg.	1
Package weight(Lbs)	41.40 lb(US) (18.78 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	24.80 in (63.0 cm)
Package 1 width	16.54 in (42.0 cm)
Package 1 Length	16.54 in (42.0 cm)

Offer Sustainability

Green Premium product REACh Declaration Yes Pro-active compliance (Product out of EU RoHS legal scope) LU RoHS
Yes
Pro-active compliance (Product out of EU RoHS legal scope) GEU RoHS
Declaration
Yes
₫Yes
☑ China RoHS Declaration
Product Environmental Profile

Contractual warranty

Warranty	18 months