

1N459/A

Small Signal Diode



DO-35

Absolute Maximum Ratings * T_a = 25°C unless otherwise noted

Symbol	Parameter	Value	Unit
V _{RRM}	Maximum Repetitive Reverse Voltage	200	V
I _{F(AV)}	Average Rectified Forward Current	500	mA
I _{FSM}	Non-repetitive Peak Forward Surge Current Pulse Width = 1.0 second Pulse Width = 1.0 microsecond	1.0 4.0	A A
T _{STG}	Storage Temperature Range	-65 to +200	°C
T _J	Operating Junction Temperature	175	°C

 $^{^{\}star}$ These ratings are limiting values above which the serviceability of the diode may be impaired.

NOTES

Thermal Characteristics

Symbol	Parameter	Value	Unit
P_{D}	Power Dissipation	500	mW
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	300	°C/W

Electrical Characteristics T_C = 25°C unless otherwise noted

Symbol	Parameter		Conditions	Min.	Max	Units
V _R	Breakdown Voltage		I _R = 100μA	200		V
V _F	Forward Voltage 1N459A		I _F = 3mA I _F = 100mA		1.0 1.0	V V
I _R		N459 I459A	V _R = 175V V _R = 175V, T _A = 150°C		25 5	nA μA
C _T	Total Capacitance 1N	I459A	V _R = 0, f = 1.0MHz		6.0	pF

These ratings are based on a maximum junction temperature of 200 degrees C.

²⁾ These are steady limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

FAST®	ISOPLANAR™	Power247™	Stealth™
FASTr™	LittleFET™	PowerEdge™	SuperFET™
FPS™	MICROCOUPLER™	PowerSaver™	SuperSOT™-3
FRFET™	MicroFET™	PowerTrench®	SuperSOT™-6
GlobalOptoisolator™	MicroPak™	QFET®	SuperSOT™-8
GTO™ .	MICROWIRE™	QS^{TM}	SyncFET™
HiSeC™	MSXTM	QT Optoelectronics™	TinyLogic [®]
I ² C TM	MSXPro™	Quiet Series™	TINYOPTO™
<i>i-</i> Lo [™]	OCX^{TM}	RapidConfigure™	TruTranslation™
ImpliedDisconnect™	OCXPro™	RapidConnect™	UHC™
FACT Quiet Series [™]		μSerDes™	UltraFET®
ACIUSS LIE DUAIU. AIDUIIU LIE WUIIU.		SILENT SWITCHER® SMART START™ SPM™	UniFET™ VCX™
	FASTr TM FPS TM FRFET TM GlobalOptoisolator TM GTO TM HiSeC TM I ² C TM I-Lo TM ImpliedDisconnect TM es TM d. Around the world. TM chise [®]	FASTrTM FPSTM MICROCOUPLERTM MicroFETTM MicroPakTM MicroPakTM MICROWIRETM MICROCOUPLERTM MICROCOUPL	FASTrTM LittleFETTM PowerEdgeTM FPSTM MICROCOUPLERTM PowerSaverTM FRFETTM MicroFETTM PowerTrench® GlobalOptoisolatorTM MicroPakTM QFET® GTOTM MICROWIRETM QSTM HISeCTM MSXTM QT OptoelectronicsTM PCTM MSXProTM Quiet SeriesTM PLOTM OCXTM RapidConfigureTM ImpliedDisconnectTM esTM OPTOLOGIC® µSerDesTM Chise® SMART STARTTM SPIMTM

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the
- 2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition		
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.		
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.		
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.		
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.		

Rev. I14