E G		
<complex-block><page-header></page-header></complex-block>		<page-header><page-header><page-header><page-header><page-header><page-header><page-header><page-header><page-header><page-header></page-header></page-header></page-header></page-header></page-header></page-header></page-header></page-header></page-header></page-header>
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Keying Shown as example Connector dimension Dim Nominal	
<ul> <li>Shell Material : Aluminium</li> <li>Shell Plating : Olive drab Cadmium</li> <li>Insulator : Thermoplastic</li> <li>Contacts : Copper Alloy</li> <li>Seals &amp; Grommet : Silicon Elastomer</li> <li>Contact Plating : Gold over copper Alloy 0.8µm minimum</li> <li>Durability : 500 Mating cycles</li> </ul>	A         34.9±0.3           B         19.07+0.1/-0.15           R         32.5Max           S         31.8±0.4           W         2.2+0.9/-0.1           VV THREAD         M15x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) $Country  Jurisdiction \& Control List \\ \hline FR \qquad Not Listed \qquad 2$ <b>PN: 8D711W99SB</b>
<ul> <li>-Delivered with Souriau contacts and Accessories</li> <li>-Temperature Range : -65°C to +175°C</li> <li>-Salt Spray : 500 hours</li> <li>-Mass : 21.28 g ± 10%</li> </ul>		A     01-10-2016     First Release       ISS     DATE     Latest modification - by       Designed By:     Date:
		TITLE     Aluminium Receptacle 8D series
→ BASIC SERIES: 8D 7 - 11 V SHELL TYPE : Jam nut Receptacle CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11	N 99 S B ORIENTA	
PLATING : W = Olive drab Cadmium	F E	JT:11-99FORMATSOURIAU DRG N°SHEETA38D711W99SB-C1/2DCBA

ſ	D I	m T		_
4	Contact Layout $\xrightarrow{F} \xrightarrow{A} \oplus$ $\xrightarrow{E} \oplus \oplus^{G} \oplus^{B} \oplus^{E} \oplus^{C}$		Panel cutout JAM NUT RECEPTACLE (TYPE 7)	4
	Contacts (Insert arrangement 11-99)           Contact position ID         Location X-axis           A         +.065 (1.65)         +.113 (2.87)           B         +.130 (3.30)         +.000 (0.00)           C         +.065 (1.65)        113 (2.87)           D        065 (1.65)        113 (2.87)           D        065 (1.65)         +.113 (2.87)           E        130 (3.30)         +.000 (0.00)           F        065 (1.65)         +.113 (2.87)           G         +.000 (0.00)         F           Sheli         Arrangement         Number of         Size         Service         Contact         Supersedes			
ى ن	sizeno.contactscontactsratinglocation11-99720IAllMS20050-99		Dim         Nominal           B         19.59+0/-0.25           ØC         20.96+0.25/-0	3
			SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)	
N			Country       Jurisdiction & Control List         FR       Not Listed         PN: 8D711W99SB	2
			A     01-10-2016     First Release     MOD N°       ISS     DATE     Latest modification - by     MOD N°       Designed By:     Date:     CUSTOMER DRAWING	
			TITLE     Aluminium Receptacle 8D series	
			SCALE     General linear     NPRDS / PROJECT       NA     Image: Description of the second source of the second	1
			SOURIAU     WWW.SOURIAU.COM     SOURIAU       it must not be reproduced or communicated without permission	
			A3 8D711W99SB-C 2/2	
	H G I	F I E	D C B A	