

1. Product profile

1.1 General description

300 W LDMOS pulsed power transistor for TCAS and IFF applications at frequencies from 1030 MHz to 1090 MHz.

Table 1. Typical performance

RF performance at $T_{case} = 25\text{ °C}$ in a common source class-AB production test circuit; $t_p = 50\text{ }\mu\text{s}$; $\delta = 2\text{ }\%$.

| Mode of operation | f (MHz) | I_{Dq} (mA) | V_{DS} (V) | P_L (W) | G_p (dB) | η_D (%) |
|-------------------|--------------|------------------|-----------------|--------------|---------------|-----------------|
| Pulsed class-AB | 1030 to 1090 | 150 | 32 | 300 | 16.5 | 57 |

CAUTION



This device is sensitive to ElectroStatic Discharge (ESD). Therefore care should be taken during transport and handling.

1.2 Features



- Typical performance at frequencies between 1030 MHz and 1090 MHz, a supply voltage of 32 V, an I_{Dq} of 150 mA, a t_p of 50 μs and a δ of 2 %:
 - ◆ Output power = 300 W
 - ◆ Power gain = 16.5 dB (typ)
 - ◆ Efficiency = 57 % (typ)
- Easy power control
- Excellent ruggedness
- High efficiency
- Excellent thermal stability
- Designed for operation in 1030 MHz to 1090 MHz band
- Internally matched for ease of use
- Compliant to Directive 2002/95/EC, regarding Restriction of Hazardous Substances (RoHS)

1.3 Applications

- RF power amplifiers for Avionics applications in the 1030 MHz to 1090 MHz frequency band

2. Pinning information

Table 2. Pinning

| Pin | Description | Simplified outline | Symbol |
|-----|-------------|---|---|
| 1 | drain |  |  |
| 2 | gate | | |
| 3 | source | | |

[1] Connected to flange

3. Ordering information

Table 3. Ordering information

| Type number | Package | | |
|-------------|---------|---|---------|
| | Name | Description | Version |
| BLA1011-300 | - | flanged LDMOST ceramic package; 2 mounting holes; 2 leads | SOT957A |

4. Limiting values

Table 4. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

| Symbol | Parameter | Conditions | Min | Max | Unit |
|-----------|----------------------|------------|------|------|------|
| V_{DS} | drain-source voltage | | - | 65 | V |
| V_{GS} | gate-source voltage | | -0.5 | +15 | V |
| I_D | drain current | | - | 15 | A |
| T_{stg} | storage temperature | | -65 | +150 | °C |
| T_j | junction temperature | | - | 200 | °C |

5. Thermal characteristics

Table 5. Thermal characteristics

| Symbol | Parameter | Conditions | Typ | Max | Unit |
|---------------|---|---|-----|------|------|
| $Z_{th(j-h)}$ | transient thermal impedance from junction to heatsink | $T_{case} = 25\text{ °C}$; $t_p = 50\text{ }\mu\text{s}$; $\delta = 2\text{ %}$; $P_L = 300\text{ W}$ | 0.1 | 0.15 | K/W |

6. Characteristics

Table 6. Characteristics

$T_j = 25\text{ }^\circ\text{C}$ unless otherwise specified.

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|---------------|----------------------------------|--|-----|------|-----|------------------|
| $V_{(BR)DSS}$ | drain-source breakdown voltage | $V_{GS} = 0\text{ V}; I_D = 3.75\text{ mA}$ | 65 | - | - | V |
| $V_{GS(th)}$ | gate-source threshold voltage | $V_{DS} = 20\text{ V}; I_D = 375\text{ mA}$ | 5.2 | 5.6 | 6.2 | V |
| V_{GSq} | gate-source quiescent voltage | $V_{DS} = 32\text{ V}; I_D = 150\text{ mA}$ | - | 5.48 | - | V |
| I_{DSS} | drain leakage current | $V_{GS} = 0\text{ V}; V_{DS} = 32\text{ V}$ | - | - | 3.3 | μA |
| I_{DSX} | drain cut-off current | $V_{GS} = V_{GS(th)} + 6\text{ V}; V_{DS} = 10\text{ V}$ | 50 | 63 | 73 | A |
| I_{GSS} | gate leakage current | $V_{GS} = 13\text{ V}; V_{DS} = 0\text{ V}$ | - | - | 60 | nA |
| g_{fs} | forward transconductance | $V_{DS} = 20\text{ V}; I_D = 24\text{ A}$ | - | 15 | - | S |
| $R_{DS(on)}$ | drain-source on-state resistance | $V_{GS} = V_{GS(th)} + 6\text{ V}; I_D = 13.5\text{ A}$ | - | 55 | 80 | $\text{m}\Omega$ |

7. Application information

Table 7. Application information

Mode of operation: Pulsed RF; $t_p = 50\text{ }\mu\text{s}$; $\delta = 2\text{ }\%$; $V_{DS} = 32\text{ V}$; $I_{Dq} = 150\text{ mA}$; $T_{case} = 25\text{ }^\circ\text{C}$; unless otherwise specified.

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|--------------------|-------------------|----------------------|-----|------|-----|------|
| P_L | output power | | 300 | - | - | W |
| G_p | power gain | $P_L = 300\text{ W}$ | 15 | 16.5 | - | dB |
| RL_{in} | input return loss | $P_L = 300\text{ W}$ | - | 10 | - | dB |
| η_D | drain efficiency | $P_L = 300\text{ W}$ | 52 | 57 | - | % |
| t_r | rise time | $P_L = 300\text{ W}$ | - | 30 | 50 | ns |
| t_f | fall time | $P_L = 300\text{ W}$ | - | 5 | 50 | ns |
| $P_{droop(pulse)}$ | pulse droop power | $P_L = 300\text{ W}$ | - | 0 | 0.2 | dB |

Table 8. Typical impedance

| f MHz | Z _S Ω | Z _L Ω |
|----------|---------------------|---------------------|
| 1030 | 4.25 – j3.57 | 1.27 – j0.33 |
| 1060 | 4.24 – j3.56 | 1.04 – j0.41 |
| 1090 | 4.47 – j3.71 | 0.91 – j0.60 |







Fig 1. Definition of transistor impedance

7.1 Ruggedness in class-AB operation

The BLA1011-300 is capable of withstanding a load mismatch corresponding to VSWR = 10 : 1 through all phases under the following conditions: $V_{DS} = 32\text{ V}$; $I_{Dq} = 150\text{ mA}$; $P_L = 300\text{ W}$; $f = 1030\text{ MHz}$ to 1090 MHz .






- (1) $f = 1030$ MHz
- (2) $f = 1060$ MHz
- (3) $f = 1090$ MHz

BLA1011-300 in a wideband circuit; $V_{DS} = 32$ V;
 $I_{Dq} = 150$ mA; $t_p = 50$ μ s; $\delta = 2$ %.

Fig 4. Load power as a function of input power; typical values



$V_{DS} = 32$ V; $I_{Dq} = 150$ mA; $t_p = 50$ μ s; $\delta = 2$ %.

Fig 5. Power gain and drain efficiency as functions of frequency; typical values

8. Test information




Table 9. List of components (see Figure 6)

To ensure good power supply of the device, adding an electrolytic capacitor close to the supply connection of the circuit may be required. The actual capacitor value may differ depending on the pulse format, the quality of the power supply and the length of the connecting wires to the power supply. In general a value of 470 μ F will be sufficient.

| Component | Description | Value | Remarks |
|-----------|---------------------------------------|-----------------------------|--------------|
| C1, C4 | multilayer ceramic chip capacitor | 62 pF | [1] |
| C2, C3 | multilayer ceramic chip capacitor | 1.5 pF | [2] |
| C5 | multilayer ceramic chip capacitor | 100 pF | [2] |
| C6, C8 | multilayer ceramic chip capacitor | 62 pF | [2] |
| C7 | multilayer ceramic chip capacitor | 10 pF | [2] |
| C9 | multilayer ceramic chip capacitor | 1.2 nF | [1] |
| C10 | electrolytic capacitor | 47 μ F; 20 V | |
| C11 | electrolytic capacitor | 47 μ F; 63 V | |
| C12 | multilayer ceramic chip capacitor | 47 pF | [1] |
| L1 | Ω -shaped enameled copper wire | d = 1 mm; length = 38 mm | |
| R1 | SMD resistor | 18 Ω | 0508 package |

Table 9. List of components (see [Figure 6](#)) ...continued

To ensure good power supply of the device, adding an electrolytic capacitor close to the supply connection of the circuit may be required. The actual capacitor value may differ depending on the pulse format, the quality of the power supply and the length of the connecting wires to the power supply. In general a value of 470 μ F will be sufficient.

| Component | Description | Value | Remarks |
|-----------|---------------------|---------------|---|
| R2 | metal film resistor | 49.9 Ω | |
| T1 | stripline | - | (W \times L) 5 mm \times 9 mm |
| T2 | stripline | - | (W \times L) 1.25 mm \times 7.5 mm |
| T3 | stripline | - | (W \times L) 15 mm \times 11 mm |
| T4 | stripline | - | (W \times L) 40 mm \times 16.8 mm |
| T5 | stripline | - | (W \times L) 1 mm \times 6.25 mm |
| T6 | stripline | - | (W \times L) 4.95 mm \times 3.55 mm |
| T7 | stripline | - | (W \times L) 9.4 mm \times 3 mm |
| T8 | stripline | - | (W \times L) 12 mm \times 2.45 mm |



[1] American Technical Ceramics type 100A or capacitor of same quality.

[2] American Technical Ceramics type 100B or capacitor of same quality.

9. Package outline

Flanged ceramic package; 2 mounting holes; 2 leads

SOT957A



DIMENSIONS (mm are the original dimensions)

| UNIT | A | b | c | D | D ₁ | E | E ₁ | F | H | L | P | Q | q | U ₁ | U ₂ | w ₁ | w ₂ |
|--------|-----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|-------|----------------|----------------|----------------|----------------|
| mm | 4.67 4.08 | 12.83 12.57 | 0.15 0.10 | 22.07 21.62 | 22.04 21.64 | 9.53 9.27 | 9.55 9.25 | 1.14 0.89 | 19.94 18.92 | 5.33 4.31 | 3.38 3.12 | 1.70 1.45 | 27.94 | 34.16 33.91 | 9.91 9.65 | 0.25 | 0.25 |
| inches | 0.184 0.1605 | 0.505 0.495 | 0.006 0.004 | 0.869 0.851 | 0.868 0.852 | 0.375 0.365 | 0.376 0.364 | 0.045 0.035 | 0.785 0.745 | 0.210 0.170 | 0.133 0.123 | 0.067 0.057 | 1.100 | 1.345 1.335 | 0.390 0.380 | 0.01 | 0.01 |

| OUTLINE VERSION | REFERENCES | | | | EUROPEAN PROJECTION | ISSUE DATE |
|-----------------|------------|-------|-------|--|---------------------|----------------------|
| | IEC | JEDEC | JEITA | | | |
| SOT957A | | | | | | 07-03-01 12-05-02 |

Fig 7. Package outline SOT957A

10. Abbreviations

Table 10. Abbreviations

| Acronym | Description |
|---------|---|
| IFF | Identification Friend or Foe |
| LDMOS | Laterally Diffused Metal Oxide Semiconductor |
| LDMOST | Laterally Diffused Metal-Oxide Semiconductor Transistor |
| RF | Radio Frequency |
| TCAS | Traffic Collision Avoidance System |
| VSWR | Voltage Standing-Wave Ratio |

11. Revision history

Table 11. Revision history

| Document ID | Release date | Data sheet status | Change notice | Supersedes |
|----------------|--|--------------------|---------------|---------------|
| BLA1011-300#3 | 20150901 | Product data sheet | - | BLA1011-300_2 |
| Modifications: | <ul style="list-style-type: none"> The format of this document has been redesigned to comply with the new identity guidelines of Ampleon. Legal texts have been adapted to the new company name where appropriate. | | | |
| BLA1011-300_2 | 20080205 | Product data sheet | - | BLA1011-300_1 |
| BLA1011-300_1 | 20070403 | Product data sheet | - | - |

12. Legal information

12.1 Data sheet status

| Document status ^{[1][2]} | Product status ^[3] | Definition |
|-----------------------------------|-------------------------------|---|
| Objective [short] data sheet | Development | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet | Qualification | This document contains data from the preliminary specification. |
| Product [short] data sheet | Production | This document contains the product specification. |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.ampleon.com>.

12.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Ampleon does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Ampleon sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Ampleon and its customer, unless Ampleon and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Ampleon product is deemed to offer functions and qualities beyond those described in the Product data sheet.

12.3 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, Ampleon does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Ampleon takes no responsibility for the content in this document if provided by an information source outside of Ampleon.

In no event shall Ampleon be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Ampleon' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Ampleon.

Right to make changes — Ampleon reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — Ampleon products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an

Ampleon product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Ampleon and its suppliers accept no liability for inclusion and/or use of Ampleon products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. Ampleon makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Ampleon products, and Ampleon accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Ampleon product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Ampleon does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Ampleon products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Ampleon does not accept any liability in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — Ampleon products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.ampleon.com/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Ampleon hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Ampleon products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Non-automotive qualified products — Unless this data sheet expressly states that this specific Ampleon product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. Ampleon accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without Ampleon' warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond Ampleon' specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies Ampleon for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond Ampleon' standard warranty and Ampleon' product specifications.

13. Contact information

For more information, please visit:

<http://www.ampleon.com>

12.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

Any reference or use of any 'NXP' trademark in this document or in or on the surface of Ampleon products does not result in any claim, liability or entitlement vis-à-vis the owner of this trademark. Ampleon is no longer part of the NXP group of companies and any reference to or use of the 'NXP' trademarks will be replaced by reference to or use of Ampleon's own Any reference or use of any 'NXP' trademark in this document or in or on the surface of Ampleon products does not result in any claim, liability or entitlement vis-à-vis the owner of this trademark. Ampleon is no longer part of the NXP group of companies and any reference to or use of the 'NXP' trademarks will be replaced by reference to or use of Ampleon's own trademarks.

For sales office addresses, please visit:

<http://www.ampleon.com/sales>

14. Contents

| | | |
|-----------|--|-----------|
| 1 | Product profile | 1 |
| 1.1 | General description | 1 |
| 1.2 | Features | 1 |
| 1.3 | Applications | 1 |
| 2 | Pinning information | 2 |
| 3 | Ordering information | 2 |
| 4 | Limiting values | 2 |
| 5 | Thermal characteristics | 2 |
| 6 | Characteristics | 3 |
| 7 | Application information | 3 |
| 7.1 | Ruggedness in class-AB operation | 4 |
| 8 | Test information | 6 |
| 9 | Package outline | 8 |
| 10 | Abbreviations | 9 |
| 11 | Revision history | 9 |
| 12 | Legal information | 10 |
| 12.1 | Data sheet status | 10 |
| 12.2 | Definitions | 10 |
| 12.3 | Disclaimers | 10 |
| 12.4 | Trademarks | 11 |
| 13 | Contact information | 11 |
| 14 | Contents | 12 |

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© Ampleon The Netherlands B.V. 2015. All rights reserved.

For more information, please visit: <http://www.ampleon.com>

For sales office addresses, please visit: <http://www.ampleon.com/sales>

Date of release: 1 September 2015

Document identifier: BLA1011-300#3