# 9001SKR2RH13 PUSHBUTTON 600VAC 10AMP 30MM SK +OPTIONS





Main	
Range of Product	Harmony 9001SK
Product or Component Type	Push-button
Device short name	9001SK
Type of operator	Spring return
Operator profile	Red recessed
Operator additional information	Extended plastic guard

#### Complementary

Bezel material	Plastic	
Mounting diameter	1.18 in (30 mm)	
Contacts type and composition	1 C/O	
Contact operation	Standard	
Mechanical durability	5000000 cycles	
Device presentation	Complete product	

#### **Environment**

LIMITOTITIETIL	
Standards	CSA C22.2 No 14
	EN/IEC 60947-5-1
	UL 508
	EN/IEC 60947-1
	JIS C 852
	EN/IEC 60947-5-4
	JIS C 4520
IP degree of protection	IP66
NEMA degree of protection	NEMA 1/2/3/3R/4/4X/6/12/13

## Ordering and shipping details

21429 - 9001 SK,SKY	
CS1	
785901042631	
1	
2.72 oz (77.111 g)	
Yes	
MX	
	CS1 785901042631 1 2.72 oz (77.111 g) Yes

### **Packing Units**

Unit Type of Package 1	PCE
Package 1 Height	5.08 in (12.903 cm)
Package 1 width	2.00 in (5.08 cm)
Package 1 Length	12.90 in (32.774 cm)

# Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EEU RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

# Contractual warranty

\Marrantv	18 months
vvarranty	18 months
•	