


SIDE VIEW



USEABLE PANEL AREA

END VIEW

Purchased assembly includes box, lid, 2 Panels and 4 cover screws Molded from FR ABS (UL94-V0) plastic

mm

[inches]

Recommended Cover screw torque -- 21-28 ozf-in (15-20 cN-m)

NOTE


Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)

(Part number and text placement/orientation on our products are subject to change, we do not recommend using them as a locating reference for modification purposes)

Contact Factory (modshop@hammfg.com) for quotes Solid models of this enclosure available in .stp or .x_t

	95.00 [3.74] 89.75 [3.53]	
45.07 28.75 34.00 [1.13] [1.34]	40.49 [1.59]	Ø2 60
	Ø5.25 [Ø.21]	_ Ø2.60 [Ø.10]

INSIDE BOTTOM



MAXIMUM PCB LAYOUT

DRAWINGS ARE AVAILABLE

Dimensions:

1552 1552C Regular Enclosure Fire Retardant ABS Grey 1552C3GY Fire Retardant ABS Black 1552C3BK **ACCESSORIES** 1552CPLGY-10 (Grey) 1552C End Panel (Pkg 10) 1552CPLBK-10 (Black) 1552C cover screw SC550-50 (Grey) [#2 X 1/2" Self-Tap] (Pkg 50) SC550BK-50 (Black) 1552C Cable gland Kit 1552CPGKITGY (Grey) [1 Cable Gland, 1 Tie Down, 2 Tie down screws] 1552CPGKITBK(Black) 1552CHGY (Grey) 1552 Wall Mount Holder 1552CHBK (Black) Tie Down Screw SC508-50 [#2 X 1/4" Self-Tap] (Pkg 50) P.C. Board Plastite Self Tapping Screw 1553WTS100 [#2 x 3/16" Self-Tap] (PKG 100)

HAMMOND MANUFACTURING. 1552C3 www.hammondmfg.com