SIEMENS

Data sheet

product type designation

product description



6GK5991-2VA00-8AA2

BA 2xRJ45VD HA

BusAdapter VD

BA 2xRJ45VD HA, bus adapter VVD (Variable Distance), for Ethernetcommunication via 2-, 4- or 8-wire-copper cables, 2xRJ45 sockets for industrial Ethernet and PROFINET, extended temperature range -40 °C...+70 °C, conformal coating, installation altitude up to 4000m, distances up to 2 wire up to 1000 m at 10 Mbit/s 2 wire up to 100 m at 100 Mbit/s 4 wire up to 300 m at 100 Mbit/s 8 wire up to 500 m at 100 Mbit/s .

| suitability for use | Ethernet transmission via 2, 4 and 8-wire line |
|--|--|
| suitability for operation | Products with BusAdapter interface (requirement: the BusAdapter is approved in the firmware of the basic unit) |
| interfaces | |
| number of electrical connections | |
| for network components or terminal equipment / maximum | 2 |
| number of 10/100 Mbit/s RJ45 ports | 2 |
| type of electrical connection | |
| for network components or terminal equipment | RJ45 |
| operating mode | |
| standard Ethernet | Yes |
| • VD | Yes; Depending on number of wires (2, 4 or 8-wire) |
| standards, specifications, approvals | |
| certificate of suitability | |
| CCC / for hazardous zone according to GB standard | Yes |
| further information / internet-Links | |
| Internet-Link | |
| to web page: selection aid TIA Selection Tool | http://www.siemens.com/tia-selection-tool |
| last modified: | 3/6/2022 🖸 |