

Specification Search

Conductive plastic element Linear taper Robust nickel-plated brass shaft and bushings PC terminals

Telecommunications

## Description

The 392 Series is a 1/2 watt potentiometer with a conductive plastic element and a molded housing. It offers an internal shaft seal for moisture protection and PC style terminals.

## Supporting Documentation Dimensions

Accessory: Knobs

| Product Specifications |   |
|------------------------|---|
| Potentiometer Type     | Industrial  |
| Element Type           | Conductive Plastic                                  |
| Terminal               | PC  |
| Power Rating           | 0.5 W   |
| Resistance Value       | 500 Ohm   |
| Resistance Tolerance   | ± 10 %  |
| Linearity              | ± 5 %   |
| Bushing Thread         | 6,35 mm [0.25 in] x 32 NEF-2A                       |
| Bushing Length         | 6,35 mm [0.25 in]                                   |
| Bushing Type           | Standard  |
| Shaft Diameter         | 3,18 mm [0.125 in]                                  |
| Shaft Length           | 22,22 mm [0.875 in]                                 |
| Shaft Ending           | Slotted   |
| Body                   | 12.7 mm [0.5 in] diameter, $\pm$ 0.79 mm [0.031 in] |

## http://sensing.honeywell.com/index.cfm?ci\_id=140301&la\_id=1&pr\_id=151925

| Electrical Taper       | Linear                              |
|------------------------|-------------------------------------|
| Operating Temperature  | -40 °C to 120 °C [-40 °F to 248 °F] |
| Working Voltage (Max.) | 350 V                               |
| Rotational Life        | 50000 cycles                        |
| Mechanical Rotation    | 295°                                |
| Availability           | Global                              |
| Series Name            | 392                                 |
| UNSPSC Code            | 4111363300                          |
| UNSPSC Commodity       | 4111363300 Potentiometers           |

Terms & Conditions | Privacy Statement | Site Map