

Protective covers - HC-STA-D07-BCSFS-PL-BK - 1419273

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Protective cover D7, for single locking latch, material: PA, protective cover material: PA, height: 30 mm, seal: no, Standard, With lanyard, diameter of retaining cord eyelet: 4 mm, for pin inserts



Key Commercial Data

Packing unit	1 pc
GTIN	4 055626 160245
GTIN	4055626160245

Technical data

Dimensions

Height	30 mm
Width	26.5 mm
Length	26.5 mm

Ambient conditions

Degree of protection (IP)	IP54
	IP65
Ambient temperature (operation)	-20 °C 100 °C

General

Note	For use on the panel mounting base
Size	D7
Туре	For supporting base element with single locking latch
Housing type	Protective cover
Color	black
Locking type	for single locking latch
Material	PA
Housing material	PA
Material, protective cover	PA



Protective covers - HC-STA-D07-BCSFS-PL-BK - 1419273

Technical data

General


Flammability rating according to UL 94	V0 (Polyamide housing)
Connection	Plastic protective cover for short-term protection

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Dimensional drawing





Dimensional drawing

Approvals

Approvals

Approvals

EAC / DNV GL

Ex Approvals

Approval details

EAC RU C-DE.AI30.B.01102



Protective covers - HC-STA-D07-BCSFS-PL-BK - 1419273

Approvals

DNV GL https://approvalfinder.dnvgl.com/ TAE000037S

Phoenix Contact 2019 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com