TRIPP-LITE

1000 Eaton Boulevard Cleveland, OH 44122 United States

Protect It! Surge Protector with 6 Rotatable Outlets, 8 ft. (2.43 m) Cord, 1080 Joules, 2xUSB Charging ports (3.4A)

MODEL NUMBER: TLP608RUSBB









Description

The TLP608RUSBB surge suppressor offers reliable surge and line noise protection. Premium features include 6 rotatable outlets, 8-ft. (2.43 m) cord in attractive black housing. The unique rotating design provides convenience and flexibility. Each outlet rotates independently to provide the perfect position to connect your equipment. The TLP608RUSBB also includes 2 USB ports with 3.4 amps of total power that offers fast charging for smartphones, tablets, MP3 players and other portable devices. 1080 joules of surge protection to handle the strongest surge. Diagnostic LED alerts you to potential wiring or protection faults before connected equipment is damaged. \$50,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

Features

- 6 rotatable outlets
- 8-ft. (2.43 m) cord
- Surge suppression rating: 1080 joules
- 3.4 amp USB Charger
- EMI/RFI noise filtering
- Diagnostic LED indicates Protected (green)
- \$50,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)
- Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required

Specifications

| OVERVIEW | |
|--------------|-----------------|
| UPC Code | 037332184665 |
| Product Type | Surge Protector |

Highlights

- 6 rotatable outlets
- 8-ft. (2.43 m) cord
- 1080 joule rating
- 3.4 amp USB charging
- Diagnostic LED

Package Includes

- TLP608RUSBB surge suppressor
- Owners Manual

TRIPP-LITE

1000 Eaton Boulevard Cleveland, OH 44122 United States

| Charging Form Factor | Strip | |
|------------------------------------|------------------------------|--|
| Device Compatibility | Phone; Tablet; Amazon Kindle | |
| INPUT | | |
| Nominal Input Voltage(s) Supported | 120V AC | |
| Recommended Electrical Service | 120V | |
| Input Cord Gauge Type | 14 gauge | |
| Input Cord Length Details | 8 ft cord | |
| Input Cord Gauge (AWG) | 14 | |
| Voltage Compatibility (VAC) | 120 | |
| Input Plug Type | NEMA 5-15P | |
| Input Cord Length (ft.) | 8 | |
| Right-Angle Plug | No | |
| Input Cord Length (m) | 2.44 | |
| Integrated Cord Clip | No | |
| OUTPUT | | |
| Frequency Compatibility | 60 Hz | |
| Output Receptacles | (6) 5-15R | |
| Circuit Breaker (amps) | 15 | |
| Transformer Accommodation | (2) Yes | |
| Right-Angle Outlets | No | |
| USER INTERFACE, ALERTS & CONTROLS | | |
| Diagnostic LED(s) | Yes | |
| CHARGING | | |
| Number of Charging Ports | 2 | |
| Total Charging Watts | 17 | |
| Charging Method | USB | |
| Charging Port Type | USB A (FEMALE) | |
| Charging Ports / Amps | (2) 3.4A | |
| Overcharge Protection | No | |
| SURGE / NOISE SUPPRESSION | | |
| AC Suppression Joule Rating | 1080 | |
| AC Suppression Response Time | < 1 ns | |



| Protection Modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression | |
|--|--|--|
| UL1449 Let Through Rating | 500, 400, 500 | |
| EMI / RFI Filtering | Yes | |
| Immunity | Conforms to IEE 587/ANSI C62.41 | |
| Automatic Shut-Off | Yes | |
| DATALINE SURGE SUPPRESSION | | |
| Cable (Coax) Protection | No | |
| Network (Ethernet) Protection | No | |
| Telephone/DSL Protection | No | |
| PHYSICAL | | |
| Material of Construction | Plastic | |
| Power Cord Color | Black | |
| Mounting Holes or Slots | No | |
| Slot or Hole Mount Measurement (Center to Center) | 255 mm | |
| Receptacle Color | Black | |
| Shipping Dimensions (hwd / in.) | 8.30 x 14.30 x 5.00 | |
| Shipping Dimensions (hwd / cm) | 21.08 x 36.32 x 12.70 | |
| Shipping Weight (lbs.) | 2.00 | |
| Shipping Weight (kg) | 0.91 | |
| Unit Dimensions (hwd / in.) | 12.930 x 2.020 x 2.070 | |
| Unit Dimensions (hwd / cm) | 32.84 x 5.13 x 5.26 | |
| Unit Weight (Ibs.) | 1.42 | |
| Unit Weight (kg) | 0.64 | |
| Input Cord Color | Black | |
| FEATURES & SPECIFICATIONS | | |
| Rotatable Outlets | Yes | |
| Antimicrobial | No | |
| GaN Technology | No | |
| STANDARDS & COMPLIANCE | | |
| Product Certifications | CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); NOM (Mexico); UL 1449; UL 1363 | |
| Product Compliance | RoHS | |
| WARRANTY & SUPPORT | | |



1000 Eaton Boulevard Cleveland, OH 44122 United States

| Product Warranty Period (Worldwide) | Lifetime limited warranty |
|--|---|
| Connected Equipment Insurance | \$50,000 Ultimate Lifetime |
| (U.S., Canada & Puerto Rico) | Insurance |



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.